



A (2:1)

TOLERANCE CLASS: ISO 2768-V  
PERMISSIBLE DEVIATIONS FOR  
LINEAR DIMENSIONS EXCEPT FOR  
BROKEN EDGES. (mm)

0.5 up to 3	over 3 up to 6	over 6 up to 30	over 30 up to 120	over 120 up to 4.00	over 4.00 up to 1000
-	±0.5	±1	±1.5	±2.5	±4

WEIGHT	
VOLUME	
WORKING PRESSURE	5 bar
MAX. FLOW	10 bar
TEST PRESSURE	4 bar
TEST FACTOR	
PAINT	powdercoated
CONNECTION TYPE	
CONNECTION DIMENSIONS	
CONNECTIONS TO BE USED WHEN ORDERING CONNECTIONS	

DESIGN	C/4
DRAWN	082207 MB
DATE/2008	
APPROVAL	
DATE/2008	
ENGINEER	
QUALITY	
PROD	
LOGISTICS	
CUSTOMER	JAGG

DESIGNATION	14-1SLM-6 P03/8 2P
ALL MEASUREMENTS REFER TO UNMOUNTED OBJECT	
REMARKS	ISO 2768-V
REPLACES	
REPLACED BY	
CONNECTED DIMENSIONS	
ORDERING NO	3100

SCALE	
DRIVING NO	3100
SCALE	
ESKZ	



278 Gewerbestraße 11, 42699 Solingen, 021 43311 - TELEFON: 021 43311

3100

3100