



## ANSER U2 SMART THERMAL INKJET

# YOU CAN GET SMART & SAVE

The U2 Smart offers the most cost-effective solution with exclusive ink portfolio for Porous & Semi-porous printing applications.

## GOOD LOOKS COUNT TOO

A compact size with 3.5-inch LCD screen provides a better user experience, while maintaining its compact body for hassle-free installation and easy integration. Includes a handy and compact remote keypad with comprehensible design for easy operation, plus a dust cover to help to protect cartridge from getting damaged in dusty environment.

## FUNCTION MAKES THE FASHION

An anti-shock mechanism design eliminates unexpected damage to your printer with a unique protective design. This printer is capable of printing crisp 1D & 2D barcodes including EAN 128, Code 128, Code 39, Data Matrix, QR Code, etc. The ink cartridge design eliminates unnecessary printhead services; it is truly zero-maintenance and has drastically decreased your total cost of ownership.

## NOTHING BEATS BRAINS

With a friendly UI & intelligent dashboard, the simple, yet elegant user interface makes for easy operation. The intelligent dashboard design monitors the printer status and provides real-time system notifications. There are multiple functions including software update, data backup and stand-alone USB keyboard operation. The U2 Smart also automatically identifies and selects the proper firing parameter to ensure the best print quality.



For additional information, contact InkJet, Inc. at  
800.280.3245 or [sales@inkjetinc.com](mailto:sales@inkjetinc.com)  
[www.inkjetinc.com/smart](http://www.inkjetinc.com/smart)



# ANSER U2 SMART

## THERMAL INKJET CODING

# THE DETAILS

### ANSER U2 SMART SPECIFICATIONS

|                                |  |
|--------------------------------|--|
| Display                        | 3.5" Color LCD with LED backlight  |
| User-interface                 | Simple and easy-to-use operating system  |
| Input Device                   | Pocket-sized IR remote keypad  |
| Available Languages            | English, Japanese, French, German, Spanish, Portuguese, Russian, Korean, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Chinese (Traditional & Simplified) |
| LED Indicators                 | Alarm, Ink low, Print, Run, Remote on/off  |
| Print Engine                   | Hewlett-Packard Thermal Ink Jet technology   |
| Print Resolution & Print Speed | 600 x 300 dpi (76.2 m/min) - Print quality is resolution & speed dependent.  |
| Print Distance                 | Recommended .24" (6mm)   |
| Print Height                   | Up to 4 lines and 0.5" (12.7mm). Selectable font size from 2.7mm, 3.6mm, 5.5mm, 8mm, 10mm, 12.7mm  |
| Print Capability               | Alphanumeric, logos, date/time, shift code, counter, lot box code  |
| Barcodes                       | EAN8, EAN13, EAN14, EAN128, UPCA, UPCE, CODE39, CODE128, TF14 (SCC-14), NVE18 (SSCC-18), C25INTER, CODABAR, PDF417, DATAMATRIX, QR CODE  |
| Electrical Requirements        | AC 100V~240V, 50/60Hz  |
| Weight                         | 1.08 lbs. (0.49kg) - excluding cartridge and bracket   |
| Dimensions (L/W/H)             | 4.5" x 3" x 2.5" (114 x 76 x 60 mm)  |
| Mounting Orientation           | Horizontal or downside   |
| Message Storage Capacity       | Store up to 999 messages   |
| Operating Temperature          | 41°F – 104°F (5°C – 40°C)  |
| Data Interface                 | RS485 & USB port   |
| Optional Accessories           |  |
| Encoder                        | Provide high print quality on unstable conveyor  |
| Photocell                      | Provide more reliable and precise sensing parameter  |
| Alarm Kit                      | Alert users in the event of an incident  |

For additional information, contact InkJet, Inc. at  
**800.280.3245** or [sales@inkjetinc.com](mailto:sales@inkjetinc.com)  
[www.inkjetinc.com/smart](http://www.inkjetinc.com/smart)

