



LVI 2018821

- Lämpötila- ja kosteusanturi mittaamaan ulko-olosuhteita
- Käyttää WM-Bus -protokollaa
- Helppo asennus seinälle
- Pitkä paristonkesto (jopa 12 vuotta) ja tarkka mittaus

myMetec - etäluentapalvelu

myMetec palvelun kautta pystyt tarkastelemaan kiinteistösi vedenkulutusta mistä tahansa milloin tahansa. Selaa kulutuksesi historiaa ja tätä hyväksikäyttämällä vähennä kulutustasi!

myMetec on jatkuvasti kehittyvä palvelu, joten sinulla on takuu paremmasta huomisesta!



Tutustu paremmin myMeteciin
www.metec.fi

Anturi sopii ulkokäyttöön lämpötilan ja kosteuden mittaamiseen ja liitetään langattomasti WM-Bus -väylän kautta osaksi järjestelmäkokonaisuutta.

Anturin lukemia on mahdollista tarkastella myMetec-palvelusta. Palvelussa on lisäksi mahdollista selata olosuhdehistoriaa!

TEKNISET TIEDOT

Käyttöjännite:	Paristo
Materiaali:	Polystyreeni
IP-suojaluokka:	IP65
Mitat (HxWxD):	110 x 100 x 52 mm
Paino:	140 g
Asennus:	Seinäkiinnitys
Lämpötila-alue:	-40°C - 55°C
Kosteusalue:	0-100 % ei kondensaatiota
Yhteys:	WM-Bus
Paristonkesto:	Jopa 12 vuotta
Takuu:	2 vuotta tai huolenpitosopimuksella sopimuksen pituuden verran



LVI 2018821

- Temperature and humidity sensor to measure outdoor conditions
- Uses the WM-Bus protocol
- Easy wall mounting
- Long battery life (up to 12 years) and accurate measurement

myMetec - remote reading service

Through the myMetec service, you can check your property's water consumption from anywhere at any time. Browse your consumption history and use it to reduce your consumption!

myMetec is a constantly evolving service, so you are guaranteed a better tomorrow!



Find out more about myMetec
en.metec.fi

This sensor is suitable for measuring outdoor temperature and humidity. The sensor is connected wirelessly to the system via the WM-Bus network.

The readings of the sensor can be viewed on the myMetec service. It is also possible to browse through the data history!

TEKNISET TIEDOT

Power:	Battery
Material:	Polystyrene
IP protection class:	IP65
Dimensions (HxWxD):	110 x 100 x 52 mm
Weight:	140 g
Mounting:	Wall
Temperature measurement range:	-40°C - 55°C
Humidity measurement range:	0-100 % no condensation
Connection:	WM-Bus
Battery life:	Up to 12 years
Warranty:	2 years or maintenance contract for the duration of the contract of care