AVALANCHE

Bottled Water Cooler





AVALANCHE

Bottled Water Cooler

The small footprint Avalanche water cooler is designed to fit conveniently on a kitchen or office countertop. The compressor in this compact design provides exceptional cooling rates and runs very quietly. Depending on the market, this cooler comes in Cold only, dual Chill and Hot and Cold models and has handy LED lights indicating when water reaches temperature. Also available as a Point-of-Use (Plumbed In) unit.




Features and Benefits

- Carrying handle makes dispenser easy to carry
- LED display indicates when cold and hot water are at the optimum temperature
- Small footprint conveniently fits kitchen or office
- Compressor operated for efficient water temperature recovery
- Stainless steel reservoir
- One piece drip tray is dishwasher safe



Carrying handle



LED display

DryGuardTM

Crystal Mountain's patented sealed-system

DryGuard[™] feature, molded from polypropylene,
protects floors against leaks
caused by cracked and faulty
bottles.



Bottled Water Cooler

Performance and Specification

General

Air cooled, bottled type water cooler provided with a power supply cord for connection to source of power supply

Cooler Cabinet

Blow molded, high density polyethylene(HDPE) Together with injunction molded bottom plate

Faucet Type

Constructed of FDA approved nylon and silicon tubing Childproof Hot water faucet

Cold Water Tank Specifications

HDPE casing with 1.1L (0.3 gal) volume Cold water cooling capacity of 2.0L (0.5 gal)/hour based on 21°C (69.8°F) room temperature

Cold Water Thermostat

Preset at factory to dispense water at temperature from 4-10°C (39.2-50°F) Adjustable cold control located at the back of the cabinet

Hot Water Tank Specifications

Stainless steel #304 casing with 1.5L (0.4 gal) volume Hot tank capacity 4.5L (1.2 gal)/hour based on 21°C (69.8°F) room temperature

Hot Water Thermostats and Heater

Automatic thermostat set at temperature range of 74-92°C(165.2-197.6°F) Manual thermostat reset in case of automatic thermostat failure ON/OFF switch for hot tank is located at the back of the cabinet

Compressor

Hermetically sealed reciprocating compressor (220~240VAC 50Hz) (100~115VAC 60Hz)

Refrigerant Type: R134a (CFC Free)

Refrigerant Charge: 28.4g (1.0 oz)

Dimensions and Freight Data Product Dimensions

368mm deep x 330mm wide x 419mm high (14.5" deep x 13.0" wide x 16.5" high)

Product Weight

H&C: 11.6kg (25.6 lb) C&C: 10.9kg (24.0 lb) Cold Only: 10.3kg (22.7 lb)

Product Boxed Dimensions

380mm deep x 370mm wide x 450mm high (15.0" deep x 14.6" wide x 17.7" high)

Product Boxed Weight:

H&C: 12.6kg (27.7 lb) C&C: 11.8kg (26.0 lb) Cold Only: 11.6kg (25.6 lb)

20FT Container Quantity: 450 Units 40FT Container Quantity: 960 Units









Website: www.crystalcoolers.com

Crystal Mountain Products Limited

North American Sales Office

11925 -145th Street Edmonton, Alberta Canada T5L 2H4 Tel: 1 800 878 6422 Tel: 1 780 454 4545 Fax: 1 780 454 9816

E-mail: sales@crystalcoolers.com

European Sales Office

Fence House, Fence Avenue Macclesfield, Cheshire United Kingdom SK10 1LT Tel: +44(0) 1625 439 111 Fax: +44 (0) 1625 502 527

E-mail: cmeurope@crystalcoolers.com

Crystal Mountain Products Inc.

US Office / Warehouse

5905 Green Pointe Drive S., Suites C-D Groveport, OH, 43125 Tel: (614) 454 1618

Fax:(614) 409 9782

E-mail: sales@crystalcoolers.com

Crystal Mountain International Limited

Hong Kong Sales Office

Room 610, Winfield Commercial Building 6-8a Prat Avenue, Tsimshatsui

Kowloon, Hong Kong Tel: (852) 2368 1989 Fax: (852) 3017 6727

E-mail: cmasia@crystalcoolers.com

