



# WOOD WAX FINISH CLEAR EXTRA THIN

Finish for oily and resinous hardwoods!



1101  
Clear Satin



## PRODUCT DESCRIPTION

Clear, satin wood finish that uniquely combines the advantages of natural oils and waxes in one product. Osmo Wood Wax Finish Clear Extra Thin is stain-resistant, water-repellent and abrasion-resistant and smoothens the surface. In comparison to conventional finishes, the use of vegetable ingredients creates a more even color and more harmonious appearance. Simple application – without primer or intermediate sanding – this is cost-effective. Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children’s toys acc. EN 71.3).

## RECOMMENDED USE

Osmo Wood Wax Finish Clear Extra Thin is suitable for the protection of wood in indoor areas: wall and ceiling paneling, wood floors, furniture and toys. Due to its water-repelling qualities, also especially well-suited for use in wet rooms (kitchens, baths, swimming pools etc.). Osmo Wood Wax Finish Clear Extra Thin is also particularly suited for the clear treatment of hardwoods rich in extractives, such as Meranti, Wenge, Merbau etc.

## INGREDIENTS

Based on natural vegetable oils and waxes (sunflower oil, soybean oil, thistle oil, carnauba wax and candelilla wax), paraffin, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). VOC content: < 500 g/liter, aliphatic hydrocarbons. Detailed declaration of ingredients available upon request.

## TECHNICAL DATA

Specific gravity: 0.85-0.87 g/cm<sup>3</sup>  
 Viscosity: 39-43s DIN EN ISO 2431/3 mm, liquid  
 Odor: faint/mild, after drying odorless  
 Flash point: > 60°C acc. DIN EN ISO 2719

## STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

## SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%). Osmo Wood Wax Finish Clear Extra Thin is ready to use. Do not thin. Stir well before use. Clean or slightly sand old microporous finishes, remove old varnish (Osmo Paint Remover or by sanding). Always wear a dust mask when sanding. Sand carefully before application starting with a coarse paper – final sanding for flooring 120 - 150 grit, furniture 220 - 240 grit. Remove dust etc. thoroughly from the surface with a brush or vacuum cleaner before application. If possible, please apply the first coat to all sides before installation. The finished surface is, among other things, influenced by the wood’s natural characteristics, therefore a trial application is recommended before finishing.



## DIRECTIONS FOR USE

Osmo Wood Wax Finish Clear Extra Thin can be brushed, wiped, dipped or sprayed in an enclosed unit.

Apply evenly along the wood grain with Osmo Flat Brush or a lint-free cloth, for example, on furniture.

1st coat: Apply thinly. Allow to dry for approx. 30 minutes under good ventilation. Wipe away any excess product. Reapply to unsaturated areas.

2nd coat: Apply thinly. Allow to dry for approx. 30 minutes under good ventilation. Wipe away any excess product.

Recommended number of coats: one coat for furniture / two coats for flooring.

For renovation works, one coat applied to the clean and dry surface is usually sufficient.

## CLEANING OF TOOLS

Clean working tools with Osmo Brush Cleaner (Benzene-free).

## DRYING TIME

Approx. 12 hours (normal climatic conditions, 73 °F/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

## COVERAGE

1 Liter covers approx. 258 ft<sup>2</sup> with one coat.

Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

## NOTE

Oils enhance the natural wood color. Applying the product too generously and insufficient ventilation lead to delays in drying time.

Caution: Apply max. one coat thinly to cabinet interiors and drawers with a cloth.

**LEAD STATEMENT: WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop.

Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING:** Combustible liquid. Keep away from flames and hot surfaces. – No smoking. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. **CAUTION:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this. **IN CASE OF FIRE:** Use for extinction: CO<sub>2</sub>, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/ container in accordance with national regulations. **KEEP OUT OF THE REACH OF CHILDREN.**

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines. Only completely emptied cans can be recycled.

## COLORS

1101 Clear Satin

## CAN SIZES

125 ml; 750 ml; 2.50 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 07/18