

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

1 Identification

Product identifier

Trade name: Osmo Liquid Wax Cleaner

Article number: 3029 clear, 3087 white

Application of the substance / the mixture
 Maintenance product
 Cleaning agent/ Cleaner

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf
 Germany

Information department: Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

Emergency telephone number: 24h-Emergency Phone Number:
 For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or Night within USA and Canada 1-800-424-9300
 Outside USA and Canada 001-703-527-3887 (WISAG FMO cargo Services GmbH & Co.KG)

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

Label elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms Void

Signal word Warning

Hazard statements H227 Combustible liquid.

Precautionary statements P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from flames and hot surfaces. – No smoking.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Observe the general safety regulations when handling chemicals.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 2)

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

Special hazards arising from the

substance or mixture Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for

containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Reference to other sections

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
64742-48-9	aliphatic hydrocarbons, C10-C13	350 mg/m ³
PAC-2:		
64742-48-9	aliphatic hydrocarbons, C10-C13	1,800 mg/m ³
PAC-3:		
64742-48-9	aliphatic hydrocarbons, C10-C13	40,000 mg/m ³

7 Handling and storage

Handling:

Precautions for safe handling

Keep receptacles tightly sealed.

Use only in well ventilated areas.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: **Osmo Liquid Wax Cleaner**

(Contd. of page 3)

Information about protection against explosions and fires:

Keep away from heat and direct sunlight.
Prevent formation of aerosols.

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).
Do not store together with oxidizing and acidic materials.

Further information about storage conditions:

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

Storage class:

10

Specific end use(s)

No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:

No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information:

The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.
Avoid contact with the eyes and skin.
Immediately remove all soiled and contaminated clothing.
Keep away from foodstuffs, beverages and feed.

Breathing equipment:

Not necessary if room is well-ventilated.

Protection of hands:

To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves

Nitrile rubber, NBR

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 4)

Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Goggles recommended during refilling.

Body protection:

Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Color:	According to product specification
Odor:	Mild

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	180-210 °C (356-410 °F)

Flash point: ~62 °C (~143.6 °F) (DIN 53213)

Ignition temperature: ~200 °C (~392 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits:

Lower:	0.6 Vol %
Upper:	7.0 Vol %

Vapor pressure at 20 °C (68 °F): <1 hPa (<0.8 mm Hg)

Density at 20 °C (68 °F): 0.77-0.80 g/cm³ (6.426-6.676 lbs/gal) (DIN 51757)

Relative density Not determined.

Evaporation rate Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 5)

Solubility in / Miscibility with

Water: Insoluble.

Viscosity:

Dynamic at 23 °C (73.4 °F): ~18 mPas (DIN 53214)

Kinematic at 40 °C (104 °F): > 20 mm²/s

Solvent content:

VOC content: 92.0 %

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability
Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

No hazardous decomposition products when stored and handled correctly.

11 Toxicological information

Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 6)

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information**Toxicity****Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h > 1000 mg/l (daphnia) (OECD 202)

EC50/ 72h > 1000 mg/l (algae) (OECD 201)

LC50 / 96h > 1000 mg/l (fish) (OECD 203)

Biolog. Abbaubarkeit (leicht abbaubar)

Persistence and degradability No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.**13 Disposal considerations****Waste treatment methods****Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**Uncleaned packagings:****Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agent:** Solvent naphtha

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS



Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 7)

14 Transport information

UN-Number <i>DOT, ADR, ADN, IMDG, IATA</i>	Void
UN proper shipping name <i>DOT, ADR, ADN, IMDG, IATA</i>	Void
Transport hazard class(es) <i>DOT, ADR, ADN, IMDG, IATA</i> Class	Void
Packing group <i>DOT, ADR, IMDG, IATA</i>	Void
Environmental hazards: <i>Marine pollutant:</i>	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

Section 355 (extremely hazardous substances):
None of the ingredients is listed.
Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
TSCA (Toxic Substances Control Act):
All ingredients are listed.
Proposition 65
Chemicals known to cause cancer:
None of the ingredients is listed.
Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 8)

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenicity categories
EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

Void

Signal word

Warning

Hazard statements

H227 Combustible liquid.

Precautionary statements

P210 Keep away from flames and hot surfaces. – No smoking.
 P262 Do not get in eyes, on skin, or on clothing.
 P271 Use only outdoors or in a well-ventilated area.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Date of preparation / last revision 04/25/2018 / 11

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS



Printing date 04/25/2018

Reviewed on 04/25/2018

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 9)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Asp. Tox. 1: Aspiration hazard – Category 1

** Data compared to the previous
version altered.*