



MAINTENANCE OIL

Ideal for refreshing and maintaining Polyx®-Oil surfaces.



3079 Clear
Matte



3081 Clear
Satin



3440 White
Transparent



PRODUCT DESCRIPTION

Clear or transparent, fast drying wood finish for the initial and routine care of oiled/waxed wood floors. Dull and matte flooring is refreshed with Osmo Maintenance Oil. By applying Maintenance Oil as needed, time-consuming sanding works and renovation can be avoided. Also suitable for changing the gloss level of intact surfaces treated with Osmo Polyx®-Oil.

Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

RECOMMENDED USE

Osmo Maintenance Oil is ideal for the maintenance of all wood floors treated with Polyx®-Oil, such as solid wood, plank, parquet, strip, OSB and cork flooring, as well as stairs and furniture surfaces. Highly recommended for public interiors (e.g. restaurants, museums and other high traffic floors).

INGREDIENTS

Based on natural vegetable oils and waxes (sunflower oil, soybean oil, thistle oil, carnauba wax and candelilla wax), paraffin, titanium dioxide white pigment, siccatives (driers) and water-repellent additives. Dearomatized white spirit (benzene-free).

VOC content: < 600 g/liter, aliphatic hydrocarbons. Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.85-0.95 g/cm³
Viscosity: 40-60s DIN 53211/3 mm
Odor: faint/mild, after drying odorless
Flash point: > 60°C acc. DIN EN ISO 2719

STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

PREPARATION

Wood surface must be clean, dry (moisture content max. 18 %) and free of dust. Clean the surface thoroughly with Osmo Intensive Cleaner and rinse (damp mop) with clear water. The finished surface is influenced by several factors, including the condition of the wood. A trial application is always recommended, especially for unfamiliar surfaces.

DIRECTIONS FOR USE

With Osmo Double Blade Trowel or Osmo Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and buff into the wood with a white pad. Remove excess product. For smaller areas, Osmo Maintenance Oil can be applied with a lint-free cloth. Allow for good ventilation while drying.

CLEANING OF TOOLS

Clean working tools with Osmo Brush Cleaner (Benzene-free).



DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 73 °F/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

COVERAGE

1 Liter covers approx. 430-645 sq. ft. with one coat. Coverage will vary depending on the type, age and texture of the wood.

NOTE

The maintenance results are influenced by several factors, including the condition of wood. Therefore, a trial application is always required. If wood is raw or already grayed, the surface must be sanded and treated with Osmo Polyx®-Oil.

WARNING

WARNING! Combustible liquid. Keep away from flames and hot surfaces. – No smoking. Use only outdoors or in a well-ventilated area. Repeated exposure may cause skin dryness or cracking. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. **IN CASE OF FIRE:** Use for extinction: CO₂, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with national regulations.

CAUTION: Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. **KEEP OUT OF THE REACH OF CHILDREN.**

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines. Only completely emptied cans can be recycled.

COLOR TONES

3079 Clear Matte
3081 Clear Satin
3440 White Transparent

CAN SIZE

1 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 07/18