

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

### 1 Identification

#### Product identifier

**Trade name:** 410 Osmo UV-Protection-Oil, colorless

**Application of the substance / the mixture**

Paint  
Coating compound/ Surface coating/ paint

#### Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf  
Germany

#### Information department:

Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de

#### Emergency telephone number:

24h-Emergency Phone Number:  
For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or Night within USA and Canada 1-800-424-9300  
Outside USA and Canada 001-703-527-3887 (WISAG FMO cargo Services GmbH & Co.KG)

### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

#### Label elements

**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms** Void

**Signal word** Warning

**Hazard statements** H227 Combustible liquid.

**Precautionary statements** P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from flames and hot surfaces. – No smoking.

P262 Do not get in eyes, on skin, or on clothing.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / protective clothing.

P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

Observe the general safety regulations when handling chemicals.  
Always wear a dust mask when sanding.

(Contd. on page 2)



**Safety Data Sheet**  
acc. to OSHA HCS



Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 2)

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**5 Fire-fighting measures**

**Extinguishing media**

**Suitable extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.

**Advice for firefighters**

**Protective equipment:** Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation  
Keep away from ignition sources

**Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Warm water and cleansing agent  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).  
Ensure adequate ventilation.

**Reference to other sections**

See Section 13 for disposal information.

**Protective Action Criteria for Chemicals**

| <b>PAC-1:</b> |                                      |                         |
|---------------|--------------------------------------|-------------------------|
| 64742-48-9    | aliphatic hydrocarbons, C10-C13      | 350 mg/m <sup>3</sup>   |
| 34590-94-8    | Dipropylene glycol monomethyl ether  | 150 ppm                 |
| 7631-86-9     | silicon dioxide, chemically prepared | 150 ppm                 |
| <b>PAC-2:</b> |                                      |                         |
| 64742-48-9    | aliphatic hydrocarbons, C10-C13      | 1,800 mg/m <sup>3</sup> |
| 34590-94-8    | Dipropylene glycol monomethyl ether  | 1700* ppm               |
| 7631-86-9     | silicon dioxide, chemically prepared | 1700* ppm               |

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 3)

| <b>PAC-3:</b> |                                      |                          |
|---------------|--------------------------------------|--------------------------|
| 64742-48-9    | aliphatic hydrocarbons, C10-C13      | 40,000 mg/m <sup>3</sup> |
| 34590-94-8    | Dipropylene glycol monomethyl ether  | 9900** ppm               |
| 7631-86-9     | silicon dioxide, chemically prepared | 9900** ppm               |

## 7 Handling and storage

### Handling:

**Precautions for safe handling**      Keep receptacles tightly sealed.  
Use only in well ventilated areas.  
Keep away from heat and direct sunlight.  
Prevent formation of aerosols.

### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

### Conditions for safe storage, including any incompatibilities

#### Storage:

**Requirements to be met by storerooms and receptacles:**      Store only in the original receptacle.  
Store in a cool location.

### Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).  
Do not store together with oxidizing and acidic materials.

### Further information about storage conditions:

Store receptacle in a well ventilated area.  
Protect from frost.  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

### Storage class:

10

### Specific end use(s)

No further relevant information available.

## 8 Exposure controls/personal protection

### Additional information about design of technical systems:

No further data; see item 7.

### Control parameters

### Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 4)

**34590-94-8 Dipropylene glycol monomethyl ether**

|     |   |
|-----|---|
| PEL | Long-term value: 600 mg/m <sup>3</sup> , 100 ppm<br>Skin  |
| REL | Short-term value: 900 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 600 mg/m <sup>3</sup> , 100 ppm<br>Skin |
| TLV | Short-term value: 909 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 606 mg/m <sup>3</sup> , 100 ppm<br>Skin |

**Additional information:** The lists that were valid during the creation were used as basis.

**Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.  
Immediately remove all soiled and contaminated clothing.  
Keep away from foodstuffs, beverages and feed.  
Avoid contact with the eyes and skin.  
Do not inhale gases / fumes / aerosols.

**Breathing equipment:**

Use suitable respiratory protective device only when aerosol or mist is formed.  
Not necessary if room is well-ventilated.  
Short term filter device:  
Filter A/P2

**Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR  
Recommended thickness of the material:  $\geq 0.4$  mm  
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

**As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

If risk of splashing:  
Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side protection)

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 5)

**Body protection:** Protective work clothing

### 9 Physical and chemical properties

#### Information on basic physical and chemical properties

##### General Information

##### Appearance:

|               |                                    |
|---------------|------------------------------------|
| <b>Form:</b>  | Fluid                              |
| <b>Color:</b> | According to product specification |
| <b>Odor:</b>  | Mild                               |

##### Change in condition

|                                     |                    |
|-------------------------------------|--------------------|
| <b>Melting point/Melting range:</b> | Undetermined.      |
| <b>Boiling point/Boiling range:</b> | > 180 °C (>356 °F) |

**Flash point:** ≥ 65 °C (≥149 °F) (DIN ISO EN 2719)

**Ignition temperature:** 240 °C (464 °F)

**Auto igniting:** Product is not selfigniting.

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

##### Explosion limits:

|               |           |
|---------------|-----------|
| <b>Lower:</b> | 0.6 Vol % |
| <b>Upper:</b> | 7.0 Vol % |

**Density at 20 °C (68 °F):** 0.95-0.97 g/cm<sup>3</sup> (7.928-8.095 lbs/gal) (DIN 51757)

##### Solubility in / Miscibility with

**Water:** Not miscible or difficult to mix.

##### Viscosity:

|                                    |  |
|------------------------------------|--|
| <b>Dynamic:</b>                    | Not determined.  |
| <b>Kinematic at 20 °C (68 °F):</b> | 60-70 s (DIN 53211/4)<br>>21 mm <sup>2</sup> /s (40°C) |

##### Solvent content:

**VOC content:** ~370 g/l / 3.08 lb/gl

**Other information** No further relevant information available.

### 10 Stability and reactivity

**Reactivity** No further relevant information available.

##### Chemical stability

##### Thermal decomposition /

##### conditions to be avoided:

No decomposition if used and stored according to specifications.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 6)

**Possibility of hazardous reactions** Reacts with fabric soaked in the product (e.g. cleaning wool).

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:**

Formation of toxic gases is possible during heating or in case of fire.  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)

**Additional information:**

CAUTION: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

## 11 Toxicological information

**Information on toxicological effects**

**Acute toxicity:**

**LD/LC50 values that are relevant for classification:**

**64742-48-9 aliphatic hydrocarbons, C10-C13**

|      |      |                               |
|------|------|-------------------------------|
| Oral | LD50 | > 5000 mg/kg (rat) (OECD 401) |
|------|------|-------------------------------|

|        |      |                               |
|--------|------|-------------------------------|
| Dermal | LD50 | > 5000 mg/kg (rat) (OECD 402) |
|--------|------|-------------------------------|

|            |           |                          |
|------------|-----------|--------------------------|
| Inhalative | LC50 / 4h | 21 mg/l (rat) (OECD 403) |
|------------|-----------|--------------------------|

**127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates**

|            |           |               |
|------------|-----------|---------------|
| Inhalative | LC50 / 4h | >5 mg/l (rat) |
|------------|-----------|---------------|

**Primary irritant effect:**

**on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**on the eye:**

No irritating effect.

**Sensitization:**

Sensitizing effect by skin contact is possible with prolonged exposure.

**Additional toxicological information:**

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

**Carcinogenic categories**

**IARC (International Agency for Research on Cancer)**

|           |                                      |   |
|-----------|--------------------------------------|---|
| 7631-86-9 | silicon dioxide, chemically prepared | 3 |
|-----------|--------------------------------------|---|

**NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 7)

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

**Toxicity**

**Aquatic toxicity:**

**64742-48-9 aliphatic hydrocarbons, C10-C13**

|                      |                                  |
|----------------------|----------------------------------|
| EC50 / 48h           | > 1000 mg/l (daphnia) (OECD 202) |
| EC50/ 72h            | > 1000 mg/l (algae) (OECD 201)   |
| LC50 / 96h           | > 1000 mg/l (fish) (OECD 203)    |
| Biolog. Abbaubarkeit | (leicht abbaubar)                |

**127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates**

|                 |   |
|-----------------|---|
| EC50 / 48h      | 3.2 mg/l mg/l (daphnia) (OECD-Richtlinie 202, Teil 1) |
| Biokonz.-Faktor | <3 (OECD-Richtlinie 305 C)                            |

**Persistence and degradability** No further relevant information available.

**Behavior in environmental systems:**

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

**Ecotoxicological effects:**

**Remark:** Harmful to aquatic life with long lasting effects.

**Additional ecological information:**

**General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

### 13 Disposal considerations

**Waste treatment methods**

**Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packagings:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleansing agent:** Solvent naphtha

(Contd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 8)

### 14 Transport information

|   |                 |
|---|-----------------|
| <b>UN-Number</b><br><i>DOT, ADR, ADN, IMDG, IATA</i>                                  | Void            |
| <b>UN proper shipping name</b><br><i>DOT, ADN, IMDG, IATA</i><br><i>ADR</i>           | Void<br>Void    |
| <b>Transport hazard class(es)</b><br><i>DOT, ADR, ADN, IMDG, IATA</i><br><i>Class</i> | Void            |
| <b>Packing group</b><br><i>DOT, ADR, IMDG, IATA</i>                                   | Void            |
| <b>Environmental hazards:</b><br><i>Marine pollutant:</i>                             | No              |
| <b>Special precautions for user</b>   | Not applicable. |
| <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>        | Not applicable. |
| <b>UN "Model Regulation":</b>   | Void            |

### 15 Regulatory information

**Safety, health and environmental regulations/legislation specific for the substance or mixture**  
*Sara*

**Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

**TSCA (Toxic Substances Control Act):**

All ingredients are listed.

**Proposition 65**

**Chemicals known to cause cancer:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 9)

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**Carcinogenicity categories**

**EPA (Environmental Protection Agency)**

None of the ingredients is listed.

**TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**

Void

**Signal word**

Warning

**Hazard statements**

H227 Combustible liquid.

**Precautionary statements**

P210 Keep away from flames and hot surfaces. – No smoking.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves / protective clothing.  
 P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** product safety department

**Contact:** Hr. Dr. Starp

**Date of preparation / last revision** 05/25/2018 / 5

**Abbreviations and acronyms:** ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 05/25/2018

Reviewed on 05/25/2018

**Trade name: 410 Osmo UV-Protection-Oil, colorless**

(Contd. of page 10)

NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flam. Liq. 4: Flammable liquids – Category 4  
Asp. Tox. 1: Aspiration hazard – Category 1

*\* Data compared to the previous  
version altered.*