



END GRAIN SEALING WAX

Special end grain sealer – protects against splitting caused by weathering!



5735 Clear



PRODUCT DESCRIPTION

Clear wood finish developed especially for sealing end grains to protect against cracks resulting from weathering. Osmo End Grain Sealing Wax minimizes water absorption as well as drying-out at end grains. Also protects from the inside as it is absorbed into wood capillaries. Swelling, shrinkage and natural oil and resin leakage are reduced.

RECOMMENDED USE

Osmo End Grain Sealing Wax is well-suited for the end grains of decking, siding or roof soffits made of hard and softwoods, such as Bangkirai, Teak, Mahogany, Garapa, Cumaru as well as Pine, Spruce, Douglas Fir, Larch, Cedar, Thermowood etc.

INGREDIENTS

Based on natural vegetable oils and waxes (sunflower-oil, soybean-oil, thistle-oil, carnauba wax, candellilla wax), paraffin, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). VOC content: < 500 g/liter, aliphatic hydrocarbons.

TECHNICAL DATA

Specific gravity: 0.88-0.95 g/cm³
 Viscosity: 25-35s DIN EN ISO 2431/4 mm, thixotropic
 Odor: faint/mild, after drying odorless
 Flash point: 45-52°C acc. DIN EN ISO 2719

STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%). The finished surface is influenced by several factors, including the condition of wood. Therefore, a trial application is always recommended, especially for unfamiliar surfaces.

DIRECTIONS FOR USE

Osmo End Grain Sealing Wax is ready to use. Do not thin. Stir well. With Osmo Flat Brush, apply generously to end grains. To achieve an optimal protection for strongly absorbent end grains, we recommend applying the sealing wax two times wet-in-wet or after drying carry out a second coat.

CLEANING OF TOOLS

Clean working tools with Osmo Brush Cleaner (Benzene-free).

DRYING TIME

Approx. 3-4 hours (normal climatic conditions, 73 °F/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

COVERAGE

1 litre covers approx. 54 ft² end grain surface with one coat.
 1 litre treats approx. 600 decking boards on both ends. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.



NOTE

Osmo End Grain Sealing Wax is clear; therefore, it can be used universally.

Please only apply to end grains. Not for area treatment. Wipe away any excess wax from other surfaces with a cloth.

Oils enhance the natural wood color. After drying, we recommend coating other wood surfaces with Osmo wood finishes, such as Decking-Oil, Country Colour or Natural Oil Woodstain.

COLOR TONES

5735 Clear

CAN SIZE

375 ml

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 07/18

WARNING

LEAD STATEMENT: WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

WARNING: FLAMMABLE LIQUID AND VAPOR. Keep away from flames and hot surfaces. – No smoking. Keep container tightly closed. Do not get in eyes, on skin, or on clothing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. **CAUTION:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this. **IN CASE OF FIRE:** Use for extinction: CO₂, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with national regulations. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING

