




ONE COAT ONLY HS^{PLUS}

Twice as much coverage through high oil content - cost-effective!



9211 White Spruce 9212 Silver Poplar 9221 Pine 9232 Mahogany 9234 Scand. Red 9262 Teak



9235 Red Cedar 9236 Larch 9241 Oak 9242 Fir Green 9261 Walnut 9264 Rosewood



9271 Ebony



PRODUCT DESCRIPTION

Transparent, satin wood finish based on natural oils for wood in outdoor areas. Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weatherproof and UV-stable. Will not crack, peel, flake or blister.

No sanding necessary, just simply recoat. Easy and seamless application. Finish stays workable while coating.

Osmo One Coat Only HS^{Plus} has a low content of solvents, works without any biocides or preservatives, has a high content of solids, so it offers high coverage. Even with a very thin coat, an optimal surface protection is achieved. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

RECOMMENDED USE

Osmo One Coat Only HS^{Plus} is ideal for the protection of all wood in outdoor areas: carports, wood siding, balconies, fences, pergolas, garden furniture and sheds. Well-suited for renewing old microporous finishes.

INGREDIENTS

Based on natural plant oil (sunflower oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and additives.

VOC content: < 400 g/liter, aliphatic hydrocarbons Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 0.95-1.2 g/cm³
Viscosity: 18-26s DIN EN ISO 2431/4 mm, viscid
Odor: faint/mild, after drying odorless
Flash point: > 61°C acc. DIN EN ISO 2719

STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.



SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%).

Osmo One Coat Only HS^{Plus} is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works.

The finished surface is influenced by the wood's natural characteristics, therefore a trial application is recommended before finishing.

If you require extra outdoor protection against rot, blue stain or mildew please contact your sales person or customer service for further instructions.

DIRECTIONS FOR USE

With Osmo Flat Brush or Microfibre Roller, apply thinly and evenly to the clean and dry wood along the wood grain and spread well.

Allow to dry for approx. 12 hours under good ventilation.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME

Approx. 12 hours (normal climatic conditions, 73 °F / 50% normal humidity). Lower temperatures and/or higher air humidity can increase the drying time.

Ventilate well while drying.

COVERAGE

1 liter covers approx. 280 ft² with one coat.

Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

Note

Transparent colors are influenced by the natural wood color, so they may deviate from the sample colors. When applied too generously, glossy spots may appear. With time, these glossy spots will weather automatically into an even satin look.

Light transparent colors offer only limited UV protection (graying and fading from exposure to sunlight); therefore they are not recommended for surfaces exposed to strong sunlight.

For exotic wood species, such as Iroko and Teak, we recommend degreasing the surface prior to application. (Test application recommended.)

Many wood species contain water-soluble colored extractives which may leach out naturally when weathered.

WARNING

LEAD STATEMENT: WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

WARNING: COMBUSTIBLE LIQUID. Keep away from flames and hot surfaces. – No smoking. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. **CAUTION:** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this. **IN CASE OF FIRE:** Use for extinction: CO₂, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with national regulations. **KEEP OUT OF THE REACH OF CHILDREN.**

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines. Only completely emptied cans can be recycled.



COLOR TONES

- 9211 White Spruce
- 9212 Silver Poplar
- 9221 Pine
- 9232 Mahogany
- 9234 Scandinavian Red
- 9235 Red Cedar
- 9236 Larch
- 9241 Oak
- 9242 Fir Green
- 9261 Walnut
- 9262 Teak
- 9264 Rosewood
- 9271 Ebony

CAN SIZES

750mL; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 07/18