



TOPOIL[®] HIGH SOLID

Oil-wax wood finish



3045 Clear satin



3056 Clear matte



3025 Neutral



3026 Acacia



PRODUCT DESCRIPTION

Osmo TopOil is a special oil and wax combination, used as a treatment on wood kitchen countertops and general interior woodwork. It is made on a base of natural plant oils and waxes. The surface is protected against common household substances, such as wine, beer, soft drinks, coffee, tea, fruit juices, milk and water. When dry, the finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and resistant to perspiration and saliva. Oils like TopOil 3056 clear enhance the natural color of wood. Osmo TopOil is food safe acc. EN 1186 Part 5 / 14.

RECOMMENDED USE

Osmo TopOil is ideal for the protection of furniture surfaces and work surfaces made of solid wood or edge-glued panels (e.g. kitchen countertops, desks, shelving etc.) in indoor areas. Also suitable for cork and OSB.

CONTAINS

Based on natural vegetable oils (sunflower-oil, thistle-oil and soyabean-oil) and waxes (carnauba wax and candelilla wax), silica, titanium dioxide, pigments, paraffins, leadfree siccatives (drying agents) and water-repellent additives. VOC content: < 450 g/liter aliphatic hydrocarbons.

TECHNICAL DATA

Specific gravity: 0.92-0.97 g/cm³
Viscosity: 50-70s DIN EN ISO 2431/4 mm, thixotropic
Odor: faint/mild, after drying odorless
Flash point: > 60°C acc. DIN EN ISO 2719

STORAGE

Shelf-life is 5 years or more if can is tightly closed.

SURFACE PREPARATION

The wood surface must be clean and dry (max. 18% moisture content).

Clean or lightly sand old microporous stains. Remove old varnishes. If necessary sand down the surface using fine sandpaper (220 - 240 grit), carefully remove dust. Always wear a dust mask when sanding. Before oiling the surface, remove sanding dust with a broom or vacuum cleaner.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always recommended, especially for unfamiliar surfaces.

DIRECTIONS FOR USE

Osmo TopOil is ready to use. Please do not thin. Shake well before use.

Apply thinly with a cloth, following the grain of the wood. Leave to dry overnight, or for at least 8 - 10 hours. Ventilate well. Repeat 2 - 3 times as described above and allow to dry for 8 - 10 hours between the applications.

For renovations, one coat applied to the clean and dry surface with a lint-free cloth is usually sufficient.

CLEANING YOUR TOOLS

Use Osmo Brush Cleaner and Thinner (benzene-free).

DRYING TIME

Approx. 8 - 10 hours (normal climatic conditions, 73 °F/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.



COVERAGE

1 litre covers approx. 258 ft² (24 m²) with one coat. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

NOTE

TopOil 3056 Clear enhances the natural wood color. TopOil 3025 Neutral counteracts this effect and protects wood almost invisibly. The natural wood color is preserved.

On dark/reddish wood species, TopOil 3025 Neutral is visible as slightly white, chalky surface.

TopOil 3026 Acacia is lightly pigmented, which gives wood an elegant look.

Applying the product too generously and insufficient ventilation lead to delays in drying time.

For cabinet interiors and drawers, apply max. one coat thinly with a cloth. Allow for good ventilation while drying.

If a higher gloss level is desired, after thoroughly drying apply Osmo Liquid Wax Cleaner thinly and polish when dry. Wood surfaces treated with TopOil are easy to maintain. Remove dust and debris with a broom or a vacuum cleaner. To clean, add Osmo Wash and Care concentrate to mop water and clean the surface with a damp (not wet!) cloth.

Use Osmo Liquid Wax Cleaner to remove tough stains. It cleans and regenerates the surface at the same time.

WARNING

LEAD STATEMENT: WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

WARNING: COMBUSTIBLE LIQUID. Keep away from flames and hot surfaces. – No smoking. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area.

CAUTION: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this. **IN CASE OF FIRE:** Use for extinction: CO₂, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with national regulations. **KEEP OUT OF THE REACH OF CHILDREN.**

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines. Only completely emptied cans can be recycled.

COLOR TONES

3025 Neutral
3026 Acacia
3056 Clear matte
3045 Clear satin

CAN SIZES

500 ml

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 07/18