



BOOM Configuration 7

The advanced technology of the new BOOM modular lightbox system combines innovation with intuition. Toolless down to its feet, BOOM is designed to help heighten your display experience. Magnetic electrical connectors light up the UL certified LED lights that come pre-installed in the profiles. Electrical wires stay hidden from view. Edge-to-edge customizable SEG backlit fabric graphics cover the front and back of the aluminum frame. Portable, configurable, desirable, BOOM is a lightbox unlike the others. BOOM is so well thought out, even its durable foam cut carry bag is made distinctly to keep all parts and pieces protected.

◆ FEATURES

Tool Free Assembly



Clean Cable Management



Magnetic Wire Connection



Tool Free Foot Connection





Display Dimensions: 235.125"W x 88.625 "H x 16.5"D

Graphic Material: Dye Sub Backlit Fabric

Graphic Finishing: Silicone beading sewn onto edge of graphic

Display Construction: Aluminum extrusion frame with plastic components

BOOM WEIGHT AND DIMENSIONS

3 Small Frames	32 lbs - 54.5"W x 15.5"H x 6.75"D (x3)	Graphic Dimensions: 39.75"W x 88.625"H
1 Medium Frame	34 lbs - 54.5"W x 15.5"H x 6.75"D (x1) 34 lbs - 45.5"W x 15.5"H x 6.75"D (x1)	Graphic Dimensions: 78.125"W x 88.625"H



INDOOR USE



DOUBLE SIDED



WARRANTY



LUMENS

Voltage (V)	24
Power (W)	450
LM/W	130
Total LM	58,500
AVG LM	5850
CU	.8
EAV	4680

LED LIGHT SPECIFICATION

Brand	Osram
Power	3W
cct (color temp)	6800K
average beam angel	20°
lm/w	130
avg lm/m²	4800 - 5800
voltage input	24V

TRANSFORMER SPECIFICATION

Power Rate 2 Transformers	95W, 252W
Certificates	UL, CE, GEM
Voltage Input	100 - 240
Voltage Output	24V




TURN AROUND TIME

4 business days after approval


1 - 5 business days for shipping

BOOM


Configuration 7 - Part List




QTY: 1
6.5 x 7.4 Ft. SEGO Modular
Lightbox Display



QTY: 3
3.3 x 7.4ft. SEGO Modular
Lightbox Display



QTY: 1
Boom Curtain Pole



QTY: 2
Graphic Curtain

