



**FOUNDATIONLESS REQUIREMENTS:**

- Centered on a square foot area that is free from cracks, seams, and walls.
- Reinforced Concrete with Pressure of 3000 psi and Soil Pressure of 2500 psf.
- Chemical anchor bolts to withstand a minimum of 2,850 lbs. of pull out force.
- Concrete must contain wire mesh reinforcement.

1) JIB CRANE FOUNDATION REQUIREMENTS ARE BASED ON A SOIL PRESSURE OF 2500 LBS PER SQUARE FOOT. CONCRETE RECOMMENDED FOR JIB CRANE FOUNDATION IS 3000 LBS PER SQUARE INCH OF COMPRESSIVE FORCE.  
2) DO NOT SCALE FROM THIS DRAWING.

**150 LB CAPACITY**

**CONFIDENTIAL**

CREATED BY: WISCOLIFT INC

**GORBEL**

600 FISHERS RUN  
P.O. BOX 593  
FISHERS, NY 14453-0593

MODEL NO: WSJ360-NP6-150-10-8

CAPACITY: 150 LBS  
SPAN: 8 FT  
H.U.B.: 10 FT  
QUANTITY: 1  
SHIPPING WT.: 408 LBS

DRAWN:	DATE: 4/13/2016
C.O.#: Sdarby00004	P/N: Sdarby00004.1A