



FOUNDATIONLESS REQUIREMENTS:

- Centered on a square foot area that is free from cracks, seams, and walls.
- Reinforced Concrete with Pressure of 3000 psi and Soil Pressure of 2500 psf.
- Chemical anchor bolts to withstand a minimum of 2,850 lbs. of pull out force.
- Concrete must contain wire mesh reinforcement.

1) JIB CRANE FOUNDATION REQUIREMENTS ARE BASED ON A SOIL PRESSURE OF 2500 LBS PER SQUARE FOOT. CONCRETE RECOMMENDED FOR JIB CRANE FOUNDATION IS 3000 LBS PER SQUARE INCH OF COMPRESSIVE FORCE.
 2) DO NOT SCALE FROM THIS DRAWING.

150 LB CAPACITY

CONFIDENTIAL

CREATED BY: WISCOLIFT INC

GORBEL

600 FISHERS RUN
 P.O. BOX 593
 FISHERS, NY 14453-0593

MODEL NO: WSJ360-NP6-150-8-14

CAPACITY: 150 LBS
 SPAN: 14 FT
 H.U.B.: 8 FT
 QUANTITY: 1
 SHIPPING WT.: 531 LBS

DRAWN:	DATE: 4/13/2016
C.O.#: Sdarby00004	P/N: Sdarby00004.1A