



4 BOLT  
 BASE BOLT PATTERN  
 7/8" BASE PLATE THICKNESS AT ANCHOR BOLT  
 VIEW A-A  
 NOT TO SCALE

**CONFIDENTIAL**

CREATED BY: WISCOLIFT INC

**GORBEL**

600 FISHERS RUN  
 P.O. BOX 593  
 FISHERS, NY 14453-0593

MODEL NO: WSJ360-NP6-150-8-16

CAPACITY: 150 LBS  
 SPAN: 16 FT  
 H.U.B.: 8 FT  
 QUANTITY: 1  
 SHIPPING WT.: 672 LBS

DRAWN:	DATE: 4/13/2016
C.O.#: Sdarby00004	P/N: Sdarby00004.1A

- FOUNDATIONLESS REQUIREMENTS:**
- Centered on a square foot area that is free from cracks, seams, and walls.
  - Reinforced Concrete with Pressure of 3000 psi and Soil Pressure of 2500 psf.
  - Chemical anchor bolts to withstand a minimum of 2,850 lbs. of pull out force.
  - Concrete must contain wire mesh reinforcement.

- 1) JIB CRANE FOUNDATION REQUIREMENTS ARE BASED ON A SOIL PRESSURE OF 2500 LBS PER SQUARE FOOT. CONCRETE RECOMMENDED FOR JIB CRANE FOUNDATION IS 3000 LBS PER SQUARE INCH OF COMPRESSIVE FORCE.  
 2) DO NOT SCALE FROM THIS DRAWING.

**150 LB CAPACITY**