

Series MPK3

系列

MPPT

MPK3-40



MPK3-60



MPK3-80



开路电压
系统电压
额定充电电流

Open circuit voltage
System voltage
Rated Charge Current

<150V
12V/24V/36V/48V
30A-100A

功能介绍

Function
introduction



MPPT



全面保护
Protections



工作参数可调
Parameters adjustable



LCD 彩显
LCD Color display



按键操作
Button mode



强制风冷散热
Forced air cooling



温度补偿
Temperature compensation



通讯端口(选配)
RS485/RJ45 port
(Optional)



产品规格

Product specification

MPPT



安装孔距— $\varnothing 5$
Mounting hole Size



MPK3-40

额定电压	额定充电电流	产品尺寸	Rated Voltage	Rated Charge Current	Product size
12V/24V/36V/48V 自动识别	30A/40A	220×200×83 mm	12V/24V/36V/48V Auto	30A/40A	220×200×83 mm



安装孔距— $\varnothing 5$
Mounting hole Size



MPK3-60

额定电压	额定充电电流	产品尺寸	Rated Voltage	Rated Charge Current	Product size
12V/24V/36V/48V 自动识别	50A/60A	265×220×88 mm	12V/24V/36V/48V Auto	50A/60A	265×220×88 mm



安装孔距— $\varnothing 5$
Mounting hole Size



MPK3-80

额定电压	额定充电电流	产品尺寸	Rated Voltage	Rated Charge Current	Product size
12V/24V/36V/48V 自动识别	80A/100A	340×240×108 mm	12V/24V/36V/48V Auto	80A/100A	340×240×108 mm

包装信息

Packaging information



MPK3-40

基本参数/Specification	30A-40A
每箱数量/Set/Carton	8PCS
每箱重量/Weight/Carton	23Kg
包装尺寸/Measurement	590×480×300mm
外箱体积/Volume/Carton	0.08CBM



MPK3-60

基本参数/Specification	50A-60A
每箱数量/Set/Carton	4PCS
每箱重量/Weight/Carton	15Kg
包装尺寸/Measurement	510×340×320mm
外箱体积/Volume/Carton	0.06CBM



MPK3-80

基本参数/Specification	80A-100A
每箱数量/Set/Carton	4PCS
每箱重量/Weight/Carton	18.5Kg
包装尺寸/Measurement	565×435×375mm
外箱体积/Volume/Carton	0.09CBM



Product display

