

Thermal Receipt Printer

HS-802

BLUNAS

- Compact Design
- High speed printing
- Multi-Connectivity options
- Easy maintenance, cost efficiency
- Best for Restaurant, Retail, grocery stores, Hospitality & etc..



Model

HS-802UL
HS-802UAI
HS-802UWB
HS-802ULAI
HS-802USL

Connectivity

USB + LAN
USB + BT
USB + WiFi + BT
USB + LAN + BT
USB + Serial + LAN

Functions

- Low noise and high speed (180mm/sec) printing
- Supporting paper 80mm (3 inch)
- Longest printer headlife (100km)
- Longest cutter life (1 million cuts)
- Support DHCP and Network printing
- Support 1D, 2D QR code printing
- With In-Built auto cutter
- Buzzer sound notification
- Support Windows, Android, IOS
- Support OPOS drivers

Application

Supermarket



Catering



Store



Tax



Bank



Medical Care



Storage



Post



Specifications


HS-802



Product Model	HS-802
Printing Parameter	
Printing method	Direct thermal
Column capacity	384 dots/line
Printing speed	180mm/S
Interfaces	USB+LAN,USB+Bluetooth, USB+WIFI+BT,USB+Serial+LAN, USB+LAN+BT
Printing paper	79.5±0.5mm×φ60mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns
Character size	ANK, Font A:1.5×3.0mm (12×24 dots) Font B:1.1×2.1mm (9×17 dots) Chinese, traditional Chinese:3.0×3.0mm (24×24 dots)
Barcode Character	
Extension character sheet	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、 PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、 West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、 PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、 PT151 (1251) etc.... 26 languages
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/ CODE93/CODE128
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes
Power	
Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 12V/2.6A
Cash drawer output	DC 12V/2A
Physical characteristics	
Weight	1.2KG
Dimensions	180×135×135mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60) humidity(10~80%)
Reliability	
Printer head life	100KM
Auto cutter	YES
Software	Support Windows, Android, IOS

Dimensions & Weight

Weight : Approx. 1200 g



Contact Us

BHAVE TECHNOLOGIES PVT LTD

#202, Maniplaza, Plotno 4,
KPHB Phase 9, Hyderabad,
India - 500085

+91 9100011766

sales@buvvas.com

www.buvvas.com