Thermal Receipt Printer

HS-88AI





Functions

- Mini size, Light weight, Durable performance
- 1500mAH, 7.4V rechargeable li-ion battery, quick charge
- Continuously work for 6 hours
- 80mm/s high printing speed
- Support various languages, easy to use

- Standard interface: USB,Bluetooth
- Support Dots Printing With different densities
- Support raster Bitmap Print
- Support 2D and 1D QR CODE Printing

Application

Supermarket

Store

Bank

Storage



Catering



Tax



Medical Care



Post



Specifications

Environment



HS-88AI Product Model **Printing Parameter** Thermal printing Printing method Resolution 8 dots/mm, 384 dots/line

Printing width 72mm (576 dots) Printing speed 50-80mm/s

Interfaces Standard: Mini-USB Port Wired Bluetooth+USB Wireless

Character ASCII9*17,12*24, GB2312-80(Chinese) Character Set ANK:(8x16,9x17,9x24,12×24), GBK: 16×16,24×24

Support Simplified & Traditional Chinese, English and Language(Code Page) other 45 kinds of International Character Sets Paper Spec

Paper Type Thermal paper Paper Width 79mm± 0.5mm Paper Roll Diameter Max: 40mm

Softwares Windows(win10/win8/win7/vista/xp/2000); Ubuntu 12.04 Drivers 32/64untu 12.04 32/64 Ubuntu 14.04 32/64

App Printer setting tools Bar codes

UPC-A, UPC-E, EAN-8,EAN13, CODE39, ITF, CODEBAR, CODE128 Etc.. 1D 2D OR Code

Indicators LED Power(red), Battery Charging(Green), Bluetooth and out of paper(Blue) Paper tore Manual **Detection Sensor** Out of Paper

Battery Rechargeable Li-ion Battery, 7.4V, 1500mAh Charger Power Supply (Adapter) Input: 100-240VAC/0.5A, 50/60Hz; Out Put: 5Vdc/2A

5°C ~ 50°C Operating Temp 10% ~ 80% Operating Humidity Storage Temp -20°C ~ 60°C Storage Humidity 10% ~ 90%

Physical characteristics 600G Weight Dimensions

Printer Headlife 30 KM

100*100*50(MM)

Dimensions & Weight

Weight: Approx. 600 g















BHAVE TECHNOLOGIES PVT LTD

#202, Maniplaza, Plotno 4, KPHB Phase 9, Hyderabad, India - 500085

+91 9133919190

sales@buvvas.com

www.buvvas.com