

Thermal Receipt Printer

HS-J80ULWB

BLUVAAS

- Best for KOT
- High speed printing
- Multi-Connectivity options
- Easy maintenance, cost efficiency
- Best for Restaurant, Retail, grocery stores, Hospitality & etc..



Model
HS-J80ULWB

Connectivity
USB + LAN +
WiFi + BT

Functions

- Low noise and high speed (250mm/sec) printing
- Supporting paper 80mm (3 inch)
- Longest printer headlife (100km)
- Longest cutter life (2 million cuts)
- Support DHCP and Network printing
- Support 1D, 2D QR code printing
- With In-Built auto cutter
- Buzzer sound notification
- Support Windows, Android, IOS
- Support OPOS drivers

Application

Supermarket



Store



Bank



Storage



Catering



Tax



Medical Care



Post



Specifications

HS-J80ULWB

Product Model	HS-J80
Printing Parameter	
Printing method	Thermal printing
Resolution	203DPI.8 dots / mm
Printing width	72mm (576 dots)
Printing speed	260mm/S
Interfaces	Standard: USB + LAN + WiFi + BT / Cash drawer Optional: Serial / Parallel / Ethernet ports Optional Wireless Communication: Bluetooth
Page mode	Supports (Optional)
Command set	ESC / POS compatible commands
Storage	
RAM	RAM 8M bytes, receive buffer area 1M bytes
FLASH	FLASH 4M bytes, NV bitmap 256K bytes
Characters	
Chinese	GB18030 24 * 24
Words, figures	ASC11 9 * 17.12 * 24
User - defined	Support
Chart	Supports different density dots and images printings Supports grating bitmap printing Supports download bitmap printing, every bitmap size should less than 256K, and the total capacity of download bitmap is 256K
Bar codes	
1D	UPC-A, UPC-E, EAN-8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
2D	PDF417, QR Code
Detection function	
Sensor	Paper out, cover opened, paper will be lack (optional), un-take out printed paper (optional)
LED indicator	
Power indicator	Green
Paper out indicator	Red
Error indicator	Red
Paper Requirement	
Type	Standard thermal receipt paper
Width	79.5 ± 0.5mm
Thickness	0.056 ~ 0.1mm
Diameter	80mm (Max)
Physical Characteristics	
Paper loading	Standard thermal receipt paper
Paper cutting	79.5 ± 0.5mm
Operating condition	0.056 ~ 0.1mm
Storage condition	80mm (Max)
Outline dimension	0.056 ~ 0.1mm
Weight	1.2 kg
Reliability	
Printer Header life	100km
Cutter life	2,000,000 times
Motor life	360,000 hours
Software function	
Driver procedure	Windows (WIN7 / WIN8 / Vista / XP / 2000) Ubuntu 12.04 32/64, Ubuntu 14.04 32/64

Dimensions & Weight

Weight: Approx. 1200 g



Contact Us

BHAVE TECHNOLOGIES PVT LTD

#202, Maniplaza, Plotno 4,
KPHB Phase 9, Hyderabad,
India - 500085

+91 9100011766

sales@buvvas.com

www.buvvas.com