

Label printer

TT426B

BLUNVAS

Best-selling Label printers lead the industry in easy-to-use features, fast printing speeds and superior reliability.



Model
TT426B

Connectivity
USB

Functions

- Equipped dual motor
- Print speed up to 127 mm/sec
- Ribbon roll capacity 300m, 25.4 mm Ribbon roller (Outer roll ribbon)
- Large visual windows
- Supporting TSPL-EZ printer language. Eltron and zebra commands
- Supports 1D 2D Barcodes
- Support Windows
- Processor 32-bit CPU

Application

Supermarket



Store



Bank



Storage



Catering



Tax



Medical Care



Post




Specifications

TT426B

Product Model	TT426B
Printing Parameter	
Printing method	Thermal Transfer / Direct Thermal
Resolution	203 DPI
Print speed	127 mm/s Max.
Print Width	108 mm (4.25")
Print Length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media thickness	0.06~0.254 mm (2.36~10mil)
Media core diameter	25.4 ~ 76.2 mm (1"~ 3")
Label length	10 - 1778 mm(0.39" ~ 70")
Label roll capacity	127 mm (5") OD (External diameter)
Ribbon capacity	Max.300m
Ribbon width	110 mm
Ribbon core inner diameter	25.4 mm (1")
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	Standard version: USB Optional:Lan/WIFI/Bluetooth/TF card
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor ④Ribbon sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL, EPL, ZPL, DPL
Physical Features	
Dimension	299 mm (D) x 235 mm (W) x 198.3 mm (H)
Weight	2.55kg
Reliability	
Print head life	30 km
Software	
Driver	Windows/Linux/Mac
SDK	Windows/Android/iOS
Power supply	
Input	AC 110-240V,1.8A, 50-60Hz
Output	DC 24V, 2.5A, 60W
Options	
Factory Options	① Built-in Ethernet server (10/100 Mbps); ② RS-232C (2400-115200 bps) communication interface; ③ Cutter ④ Peeling machine ⑤ Bluetooth module ⑥ WiFi module
Dealer Options	① External paper roll holder and 1"paper roll; ② Extension board for external paper roll holder
Environmental Conditions	
Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity:10 ~ 90% non-conde

Dimensions & Weight

Weight : Approx. 2.5 kg



Contact Us

BHAVE TECHNOLOGIES PVT LTD

#202, Maniplaza, Plotno 4,
KPHB Phase 9, Hyderabad,
India - 500085

+91 9100011766

sales@buvvas.com

www.buvvas.com