TP-LINK[®]

54M Wireless USB Adapter TL-WN321G



Wireless Roaming, light and flexible, can move among different AP with no break

Provides soft AP Mode, supports PSP connection*

Up to 54Mbps wireless rate and fully compatible with 802.11b.



Description:

The TP-LINK TL-WN321G Wireless USB Adapter gives you the flexibility to install the PC or notebook PC in the most convenient location available, without the cost of running network cables.

Its auto-sensing capability allows high packet transfer up to 54Mbps for maximum throughput, or dynamic range shifting to lower speeds due to distance or operating limitations in an environment with a lot of electromagnetic interference. It can also interoperate with all the 11Mbps wireless (802.11b) products. Your wireless communications are protected by up to 128-bit encryption, so your data stays secure.


Additionally, TL-WN321G supports soft AP Mode, and PSP connection*, which brings you joyful Online-gaming experience.

www.tp-link.com

Specifications:

Standards	IEEE 802.11g IEEE 802.11b
Interface	A-type USB 2.0 Connector
Wireless Signal Rates With Automatic Fallback	11g: 54/48/36/24/12/9/6 Mbps (Auto -Sensing) 11b:11/5.5/2/1 Mbps (Auto -Sensing)
Frequency Range	2.4-2.4835GHz
Wireless Transmit Power	15dBm(typical)
Modulation Type	DBPSK, DQPSK OFDM, CCK
Receiver Sensitivity	54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Antenna Type	Internal Omni Directional, 0dBi
Wireless Security	64/128 bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)
Media Access Control	CSMA/CA with ACK
Range	Indoors up to 100m, outdoors up to 300m. (Standard transmission distance, it is limited in different environment.)
Certifications	CE, FCC
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Relative Humidity	10% ~ 90%, non condensation
Storage Humidity	5%~95% non-condensing
Dimensions	3.4x0.9x0.4(in.), 86.5x24x10(mm)

Diagram:



Features:

- USB 2.0, portable and flexible
- Supports Ad-Hoc/Infrastructure modes
- Provides soft AP Mode, and PSP connection*
- Supports 54/48/36/24/18/12/9/6Mbps or 11/5.5/2/1Mbps data transfer rates
- Supports 64/128/152 strength WEP encryptions, as well as WPA/WPA2 and WPA-PSK/WPA2-PSK encryptions and mechanisms
- Supports Windows 2000, XP, Vista
- Provides simple configuration and supervisor program
- * PSP connection is supported by Windows 2000, XP only.

Package:

- 54M Wireless USB Adapter TL-WN321G
- 100cm USB Extension Cable
- Quick Setup Guide
- Resource CD, including:
 - •TL-WN321G Wireless Client Utility and Drivers
 - · User Guide
 - · Other Helpful Information

Related Products:

- 54M Wireless Router TL-WR340GD
- 54M Wireless Cardbus Adapter TL-WN353GD
- ADSL2+ Modem Router TD-8810

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specificationsmay be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies Co., Ltd.

Copyright © 2009 TP-LINK Technologies Co., Ltd. All rights reserved.

www.tp-link.com