

Item # _____

Qty # _____

Model # _____

Project # _____



DUKERS

Quality Commercial Refrigeration

GAS RANGE

DCR24-GM / 24" Griddle Top Gas Range



Casters are inside the oven



Knobs



Cooking Surface



PRODUCT DESCRIPTION

- ✦ Stainless steel exterior including front, back sides, kick plate, back guard and over shelf
- 🍳 Heavy duty 12" X 12" removable, cast iron top grates
- 🌡️ Oven temperature range between 175°F to 500°F
- 🔌 3/4" NPT rear gas connection and regulator standard.
- 🍽️ Two(2) chrome oven rack per oven standard, multiple position oven rack guides
- 🍳 Enamel interior oven for easy cleaning.
- 🛞 6" casters with lock for easy mobility.



HIGH QUALITY STAINLESS STEEL & ROBUST DESIGN

GAS RANGE MODEL	DIMENSION		
	Width	Depth	Height
DCR24-GM	24 in	31 1/2 in	56 in



Los Angeles | San Francisco | Dallas
Houston | Florida | Chicago | New Jersey

📞 1-800-931-8628


@ info@dukersusa.com

www.DukersUSA.com


DETAILS & SPECIFICATIONS

DCR24-GM


Front View



Side View



Top View



SANITATION



US

Conforms to NSF/ANSI7 (ETL)



Product Specifications

WORKING AREA 24" x 20"
GAS TYPE LPG/NG

BURNERS
SINGLE OUTPUT BTU
NOZZLE #
TOTAL OUTPUT BTU
GAS PRESSURE

	LPG		NG	
	GRIDDLE	OVEN	GRIDDLE	OVEN
BURNERS	2	1	2	1
SINGLE OUTPUT BTU	26000 BTU	30000 BTU	26000 BTU	30000 BTU
NOZZLE #	53	52	43	40
TOTAL OUTPUT BTU	82000 BTU		82000 BTU	
GAS PRESSURE	10		5	

Model	Packaging Dimensions (inches)			Net Weight (lbs)	Ship Weight (lbs)	Container Capacity 40'HQ
	W	D	H			
DCR24-GM	26"	36 4/5"	38 1/5"	304.70	370.70	86



Los Angeles | San Francisco | Dallas
Houston | Florida | Chicago | New Jersey

1-800-931-8628

@ info@dukersusa.com

www.DukersUSA.com