

## DIN-4SH



**Tube:** Oil resistant, synthetic rubber

**Reinforcement:** Four spirals of high tensile wire

**Cover:** Oil and weather resistant synthetic rubber

**Temperature:** -40° F / +212° F, Intermittent use up to 250° F

**Application:** Petroleum based hydraulic fluid, gasoline, water, diesel fuels, lubricating oils, glycol, mineral oils, and more

**Termination:** 400 series, non skive, 1-piece fitting

**Key Note:** High impulse cycles

Part Number	Hose I.D.	Hose O.D.		Max Working Pressure (psi)	Minimum Burst Pressure (psi)	Minimum Bend Radius		Weight (lbs/ft)	Termination
	(in)	(in)	(mm)			(in)	(mm)		(lbs/ft)
4SH-12	3/4"	1.29	32.5	6,090	24,360	11	280	1.14	400/1-piece
4SH-16	1"	1.52	38.7	5,510	22,040	13.4	340	1.68	400/1-piece
4SH-20	1-1/4"	1.82	46.2	5,000	20,000	18.1	460	2.02	400/1-piece
4SH-24	1-1/2"	2.11	53.5	4,205	16,820	22	560	2.42	400/1-piece
4SH-32	2"	2.68	68	3,625	14,500	27.6	700	3.36	400/1-piece