



### **Hazardous Cupboard Sizes Available:**

<b><u>Height</u></b>	<b><u>Width</u></b>	<b><u>Depth</u></b>	<b><u>Shelves Supplied</u></b>	<b><u>Sump Capacity</u></b>
1800mm	900mm	460mm	3	14 Litres
1800mm	1200mm	460mm	3	18 Litres
1200mm	900mm	460mm	2	14 Litres
900mm	460mm	460mm	1	7 Litres
900mm	900mm	460mm	1	14 Litres
700mm	350mm	300mm	1	3 Litres
700mm	900mm	460mm	1	14 Litres
<b>(Mobile Cupboard)</b> 1040mm	900mm	460mm	1	-
<b>(Mobile Cupboard)</b> 840mm	900mm	460mm	1	-
<b>(Floor Chests)</b> 610mm	1170mm	460mm	-	20 Litres
<b>(Floor Chests)</b> 510mm	610mm	340mm	-	7 Litres
<b>(Wall Mounted)</b> 570mm	850mm	255mm	1	<b>No Sump Fitted</b>

### **Cupboard Construction:**

- 0.7mm mild steel, pop riveted carcass construction
- Integral liquid-tight sump fitted at the bottom of the cupboard (Except Wall Mounted Cupboard)
- Door aperture has return bends to eliminate open gaps
- Delivered fully assembled
- Warning labels supplied
- Reaction to Fire Classification EN 13501-1 – Supporting documents available
- ‘No Snag’ handles with 2-point locking mechanism
- Adjustable spill-retaining galvanised shelves for superior spill management with a UDL of 70KG

- Cupboard stands are available which raise the cupboards by 500mm and have an adjustable foot for uneven surfaces
- **Floor Chest Construction** - Material: 1.5mm Mild Steel
- **Floor Chest Construction** - Fully welded integrated sump & angled lid to discourage article placement
- **Floor Chest Construction** - Fully welded construction with 2 no. welded 2.5" butt hinges.
- **Floor Chest Construction** - Connected to carcass with 4.8mm pop rivets.
- **Floor Chest Construction** - Fitted with restraint to prevent lid from falling back.
- **Floor Chest Construction** - Supplied with Hasp and Staple (Padlock not supplied)

### **Cupboard Sump Construction:**

- Material: 1.2mm Mild Steel
- Fully welded seams
- Sump Integral

### **Cupboard Door Construction:**

- Material: 0.9mm Mild Steel. A stiffener is spot welded vertically in the centre of the door with two 2½" butt hinges spot welded to the door. The door is attached to the carcass via the hinges, with 4.8mm pop rivets. The door has two-point locking with an all metal key locking handle.

### **Carcass & Door Paint Finish:**

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard anti-bacterial compound
- Powder coated with a special paint - **Truflow Yellow**

### **Cleaning & Maintenance:**

- Clean paint work periodically with warm soapy water or Foaming cleaner
- Oil hinges and lock sparingly as required with a light oil (3in1 or similar)

Tel: 0121 702 1659    Email: [info@firstmats.co.uk](mailto:info@firstmats.co.uk)

