



## Commercial Black Rubber General purpose grade for water applications and diluted chemicals

- Versatile 'general purpose' grade rubber sheeting, often used in marine applications.
- Ideal for low cost waterproof seals and gaskets.
- 68 degrees shore A hardness.
- Tensile strength at break: 3.0 Mpa.
- Elongation at break: 200%.



### Size Options

Size	Colour	Weight (kg)
1.4 m x 10 m x 1.5 mm	Black	36
1.22 m x 10 m x 3 mm	Black	
1.4 m x 10 m x 3 mm	Black	68.65
1.4 m x 10 m x 4.5 mm	Black	104.1
1.4 m x 10 m x 6 mm	Black	136.05
1.4 m x 5 m x 8 mm	Black	88.8
1.4 m x 5 m x 10 mm	Black	115.55
1.4 m x 5 m x 12 mm	Black	130.85
1.4 m x 5 m x 20 mm	Black	225
1.4 m x 5 m x 25 mm	Black	270

### Technical Specifications

<b>Material</b>	SBR
<b>Surface Finish</b>	Smooth
<b>Product Height</b>	1.5 mm-25 mm
<b>Roll Lengths</b>	5 m, 10 m
<b>Min. Operating Temperature</b>	-30°C
<b>Max. Operating Temperature</b>	+80°C
<b>Resistance to Chemicals</b>	Resistant to dilute chemicals
<b>Other Product Performance</b>	Test Temperature 25°C Relative Humidity 35% Test by GB5574-94 Correlation criterion GB/T528-1998 GB/T3512-1989 GB/T531-1992