



## High Wear-Resistant Anti-Fatigue Mat

- Exceptional fatigue-relief properties – a real investment for the workplace.
- Dual layer construction for superior comfort and durability.
- Tough textured top surface for excellent resilience against wear and tear.
- Insulates against the effects of cold concrete floors.
- Low density under layer provides extremely effective underfoot cushioning.
- Ideal for demanding locations, especially where regular turning is involved.
- Tapered edges to reduce trip hazards.
- Range of colours available.
- Fire tested to BS EN 13501-1.

### Parts

Size Options	Colour	Weight (kg)
0.6 m x 0.9 m	Black	2
0.9 m x 1.5 m	Black	4.99
0.9 m x 18.3 m	Black	61
0.9 m x per linear metre	Black	3.8
0.9 m x 3.65 m	Black	12.15
0.6 m x 18.3 m	Black	45.6
0.6 m x per linear metre	Black	2.49
1.2 m x 18.3 m	Black	93.5
1.2 m x per linear metre	Black	5.1

### Technical Specifications

<b>Material</b>	Open Cell PVC (Foam)
<b>Surface Finish</b>	Pebble
<b>Product Height</b>	12.5 mm
<b>Roll Length</b>	18.3 m
<b>Min. Operating Temperature</b>	0°C
<b>Max. Operating Temperature</b>	+60°C
<b>Environmental Resistance</b>	Suitable for dry indoor environments
<b>Typical Applications</b>	Production lines, Assembly areas, Packing stations, Workbenches, Retail counters
<b>Installation Method</b>	Loose lay
<b>Cleaning Method</b>	Brush/mop the top surface
<b>Fire Tested to</b>	BS EN 13501-1 Class Dfl - s1
<b>Guarantee</b>	2 years when used in a dry