



Commercial Black Neoprene Rubber

High resistance to mineral oils,
greases, dilute acids and alkalis

- Good ageing and weathering properties, ideal for outdoor use
- Heat, chemical, oil fire and ozone resistance
- 65 degrees shore A hardness.
- Tensile strength at break: 6.0 Mpa.
- Elongation at break: 250%.



Size Options

Size	Colour	Weight (kg)
1.4 m x 10 m x 3 mm	Black	61.4
1.4 m x 10 m x 4.5 mm	Black	90.55
1.4 m x 10 m x 6 mm	Black	125
1.4 m x 5 m x 10 mm	Black	109
1.4 m x 5 m x 12 mm	Black	126.6
1.4 m x 5 m x 20 mm	Black	236
1.4 m x 5 m x 25 mm	Black	290

Technical Specifications

Material	CR and SBR
Surface Finish	Smooth
Product Height	3 mm-25 mm
Roll Lengths	5m, 10m
Min. Operating Temperature	-20°C
Max. Operating Temperature	+80°C
Resistance to Chemicals	Excellent resistance to mineral oils, greases, dilute acids and alkalis
Other Product Performance	Test Temperature 25°C Relative Humidity 35% Correlation criterion GB/T528-1998 GB/T3512-1989 GB/T531-1992