

Standard sizes:

| | |
|-----------------------|-----------------------|
| Product | Slipline |
| Height | 6mm (1/4") |
| Standard roll options | 10 x 0.6m (33' x 2') |
| | 10 x 0.91m (33' x 3') |
| Weight | 3.70kg/m ² |
| | (0.76lb/sq.ft) |

Tolerances:

| | Height (+/- 0.5mm) | Length (0+0.3m) | Width (+/- 1cm) |
|-----------|--------------------|-----------------|-----------------|
| Floorline | 6mm | 10m | 60cm 91cm |

All dimensions are nominal

Technical information:

| | |
|-----------------|---|
| Acoustic | Excellent sound absorption |
| Chemical | Resistant to most acids, alkalines and oils. |
| Composition | Flexible Polyvinyl Chloride (PVC) |
| Environment | Slipline is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.. |
| Fire | DIN 4102 Part 1- Classification B2. BS 2782 Part 1, method 140A: 1992 (ISO 1210: 1992) |
| Hygiene | Made from non-porous PVC that's naturally resistant to bacteria growth. Incorporates anti-microbial and anti-fungal additives for continuous hygiene. |
| Reversion | Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. |
| Slip resistance | ASTM F 1677 - Dry/Wet: 1.0/0.8 DIN51130: R11, V10 DIN51097: Classification C |
| Thermal | Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes. |
| UV light | Resistant to PVC degradation. The red colour isn't colourfast in direct sunlight. |
| Warranty | One year. |

Installation:

Slipline's one-piece construction means installation is

simple:

- Comes in 10m rolls
- Easy to cut to fit on site
- No special tools or previous site visits needed
- Contours to uneven surfaces