


Ultimate Grip Anti-Fatigue Mat

Reduce slips and standing fatigue in one

- Provides both slip-resistance and fatigue-relief.
- 'Grit' coating and raised surface pattern combine for highly effective slip resistance.
- Material composition means it is highly resistant to chemicals, oils and grease.
- Provides fatigue-relief from cold hard floors.
- Ideal for demanding locations such as engineering workshops.
- Moulded bevelled edges reduce trip hazards.
- Open drainage holes for spilt liquids.
- Slip tested to DIN 51130.



Parts

| Size Options | Colour | Weight (kg) |
|---------------|--------|-------------|
| 0.9 m x 1.5 m | Black | 9.3 |

Technical Specifications

| | |
|--------------------------------|--|
| Storage and application | Store at room temperature, free from deformations. |
| Tensile Strength | ASTM D412, 5 (+/-1)Nm/mm ² |
| Elongation | ASTM D412, 250% (+/-50%) |
| Application Temperature | 18°C to 82°C |
| Slip Tested to | DIN 51130 - R13 |
| Manufacturing process | Compression moulding |

Technical Specifications

| | |
|-----------------------------------|--|
| Material | NBR |
| Natural Material Content % | 65 |
| Surface Finish | Carbide bonded to rubber with holes to allow drainage |
| Product Height | 13 mm |
| Product Weight | 11 kg |
| Hole Size | 21 mm |
| Max. Operating Temperature | +70°C |
| Resistance to Chemicals | Resistance to mineral oils and animal fats |
| Environmental Resistance | Suitable for oily environments |
| UV Resistance | Moderate |
| Typical Applications | Demanding locations e.g. Engineering workshops, Machine tool areas where swarf is prevalent. Ideal for Oil & Gas industry. |
| Installation Method | Loose lay |
| Cleaning Method | Pressure hose with mild detergent or pass through commercial dishwasher |