






Weld-Diamond Anti Fatigue Welding Mats

- Welders need relief from standing like any other professional.
- The heavy-duty top surface is both resilient and fire tested, whilst the soft foam underlayer provides cushioning for the feet.
- Ideal for welding bays and demanding industrial use.
- Flame retardant top surface (tested to BS EN 13501-1) – so weld sparks aren't an issue.
- Loose lay – can be moved easily.
- Bevelled edges help avoid creating a trip risk.



Parts

Size Options	Colour	Weight (kg)
0.6 m x 0.9 m	Black	3.7
0.9 m x 1.5 m	Black	9.32
0.9 m x 18.3 m	Black	113
0.9 m x per linear metre	Black	6.5

Technical Specifications

Material	Vinyl top surface with PVC foam backing (fusion bonded, not glued)
Surface Finish	Diamond pattern
Product Height	15 mm
Roll Length	18.3 m
Min. Operating Temperature	0°C
Max. Operating Temperature	+55°C
Environmental Resistance	Suitable for dry indoor environments. Will withstand welding splatter and spillages of other hot materials.
Typical Applications	Welding bays
Installation Method	Loose lay
Cleaning Method	Brush/mop the top surface
Fire Tested to	BS EN 13501-1 Class Cfl - s1