TAR-GET

Page: 1

Compilation date: 27-10-2017

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** TAR-GET **Product code:** 100045

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

## 1.3. Details of the supplier of the safety data sheet

Company name: CLEANERCAR IRELAND

WEST LINK BUSINESS PARK

OLD MALLOW ROAD

CORK

**IRELAND** 

**Tel:** 087 985 9428

Email: info@cleanercar.ie

## 1.4. Emergency telephone number

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Acute Tox. 4: H312+H332; Flam. Liq. 3: H226

Most important adverse effects: Flammable liquid and vapour. Harmful in contact with skin or if inhaled Causes skin

irritation.

### 2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H312+H332: Harmful in contact with skin or if inhaled

H315: Causes skin irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280: Wear protective gloves and eye protection.

TAR-GFT

Page: 2

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P302+P352: IF ON SKIN: Wash with plenty of water.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### Hazardous ingredients:

#### **XYLENE**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	30-60%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

### HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

926-141-6	_	-	Asp. Tox. 1: H304	30-60%	
			· ·	1	

## AMIDES, COCO, N,N-BIS(HYDROXYETHYL)

271-657-0 686	603-42-9 -	Skin Irrit. 2: H315; Eye Irrit. 2	:: H319 1-10%
---------------	------------	-----------------------------------	---------------

## Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises. A decontamination shower

TAR-GFT

Page: 3

should be available on the premises. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

#### Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

TAR-GET

Page: 4

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

### **Hazardous ingredients:**

#### **XYLENE**

### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
IE	221 mg/m3	442 mg/m3	-	1

#### **DNEL/PNEC Values**

DNEL / PNEC No data available.

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Solvent

Solubility in water: Insoluble

Viscosity: Viscous

Flash point°C: 23 - 60 Relative density: 0.85

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

TAR-GET

Page: 5

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong bases. Strong reducing agents.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

### Hazardous ingredients:

#### **XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

## Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM	Hazardous: calculated
Skin corrosion/irritation DRM		Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

TAR-GET

Page: 6

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

## 14.1. UN number

UN number: UN1993

# 14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(XYLENE)

## 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

## **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

TAR-GET

Page: 7

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

## **Section 16: Other information**

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H312+H332: Harmful in contact with skin or if inhaled

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.