

AtticFoil® Radiant Barrier Supply, LLC

8611 Normandy Way
Argyle, TX 76226
800-595-8772

www.AtticFoil.com
support@AtticFoil.com

Original AtticFoil® Radiant Barrier Foil – Vapor Barrier

Solid, double-sided, heavyweight, pure aluminum product

Thermal Performance ASTM E408	Reflectivity 97% Emissivity 0.03
Weight	28.6 lb per 1,000 ft ²
Thickness	0.005 inches (5 mils)
Fire Rating ASTM E84	Class A/ Class 1
Water Vapor Permeability ASTM E96	<0.02 perms (0.005 g/m ² per day)
Tensile Strength ASTM D828	83.7 lb/in machine direction 70.1 lb/in cross direction
Flame Spread ASTM E84	10
Smoke Development ASTM E84	10
Oxidation & Delamination	None
Toxicity	This product does not contain any toxic or poisonous agents that may be harmful to the human body and wildlife when exposed thereto or during handling.
Temperature range ASTM C411	-76°F to 212°F (avoid temperatures above 300°F)



AtticFoil® solid, double-sided material structure: 3 layers of material + 2 layers of PE laminating

All testing done via: UNITED STATES TESTING COMPANY, INC.

AtticFoil® Radiant Barrier Supply, LLC is a proud member of the BBB and has carried an A+ rating since 2007.