



## JET SPIKE 310-90, 310-180, 310-360

Adjustable Flow Spray on Spike

### APPLICATIONS

This adjustable spray comes ready to install. It is ideal for flower beds, ground cover and potted plants.

### FEATURES

- 31 cm spray on spike
- 20 cm extension
- Total height of spike with extension : 51 cm
- Micro-spray head made of acetal, spike made of polyethylene and extension made of HDPE
- 4/6 mm, pre-mounted, flexible PVC connection tube (length: 50 cm)

### SPECIFICATIONS

Pressure : 0.5 to 2.5 bar  
Flow: 0 to 130 litres/hour  
Radius : adjustable from 0 to 4.2 m

### MODELS

JET SPIKE 310-90: 90° micro-sprinkler on spike  
JET SPIKE 310-180: 180° micro-sprinkler on spike  
JET SPIKE 310-360: 360° micro-sprinkler on spike with 18 jets



### PERFORMANCE

bar	90°		180°		360°	
	m	l/h	m	l/h	m	l/h
0,5	0 - 1,7	0 - 58	0 - 1,9	0 - 58	0 - 2,5	0 - 58
1,0	0 - 2,5	0 - 82	0 - 2,3	0 - 82	0 - 3,4	0 - 82
1,5	0 - 2,9	0 - 101	0 - 2,7	0 - 101	0 - 3,9	0 - 101
2,0	0 - 3,2	0 - 117	0 - 3,0	0 - 117	0 - 4,1	0 - 117
2,5	0 - 3,5	0 - 130	0 - 3,3	0 - 130	0 - 4,2	0 - 130

## XS-360TS-SPYK

Adjustable Flow Micro-spray on Spike

### APPLICATIONS

This micro-spray with full circle pattern is shipped ready to install. Ideal for flower beds, ground cover, potted plants, etc.

### FEATURES

- Micro-spray mounted on 12.7 cm spike
- 360° spray pattern
- Shipped with 4-6 mm barb connection for

installation into 13-16 mm tubing  
• Excellent distribution uniformity

### SPECIFICATIONS

Pressure: 1 to 2.0 bar  
Flow: adjustable from 0 to 90 l/h  
Radius: adjustable from 0 to 2.0 m

### MODEL

XS-360TS-SPYK: Adjustable flow micro-spray on spike



bar	m	l/h
1,0	0-1,4	0-64
1,5	0-1,8	0-78
2,0	0-2,0	0-90

## XS-90, XS-180, XS-360 SERIES

Adjustable Flow Sprays

### APPLICATIONS

These sprays have a uniform emission pattern to provide excellent distribution. Adjustable flow/radius by turning integral ball valve. Ideal for ground cover and annual flower beds.

### FEATURES

- Uniform emission pattern and excellent distribution
- 10-32 self-tapping threads fit into stake and riser assembly (PFR/RS)

### MODELS

XS-90: Adjustable flow/radius 90° spray  
XS-180: Adjustable flow/radius 180° spray  
XS-360: Adjustable flow/radius 360° spray



### PERFORMANCE

bar	XS-90		XS-180		XS-360	
	m	l/h	m	l/h	m	l/h
0,5	0-1,5	0-53	0-1,9	0-53	0-2,5	0-53
1,0	0-2,4	0-78	0-2,4	0-78	0-3,4	0-78
1,5	0-2,9	0-98	0-3,0	0-98	0-4,1	0-98
2,0	0-3,1	0-115	0-3,2	0-115	0-4,1	0-115
2,5	0-3,3	0-130	0-3,4	0-130	0-3,6	0-130