

Product Classification

Type of floor covering Yarn type		Multi-Level Loop Carpet Tile Solution Dyed Nylon	
Warranty*	Commercial - available upon request	15 years	

*All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the commercial warranty, contact your Armstrong Flooring representative.

Colours (Standard)	_	6	
Dimensions	ISO 24342	500mm x 500mm	
Gauge	-	1/10th	
Pile weight	-	450g/m² (± 25.0g)	
Overall thickness	-	6.0mm (± 1.0mm)	
Pile height	-	3.0mm (± 0.5mm)	
Backing	=	HP Bac II	
Stain resistance treatment	-	Yes	
Tiles/carton	-	20	
m²/carton	-	5.0	
m²/pallet	-	180.0	
kg/carton	-	15.0	

Installation

To current AS/NZS 2455.1&
AS2455.2 (latest versions) and
Armstrong Flooring Installation
Instructions - Carpet Tiles

1/4 Turn, Ashlar, Brick

Sustainability

Castallability		
Backing minimisation	-	PVC & Bitumen Free
Carpet & Rug Institute	-	CRI Green Label + Plus
TVOC emissions	_	Compliant with Green Building Council low emitting VOC emission rates

Technical Performance

Fire resistance	AS ISO 9239-1 Critical Radiant Flux (CHF Value) Smoke Development Rate	≥ 4.5kW/m² ≤ 750%.min		
Colour fastness	ISO 105-B02, Method 3	≥ 6		
Dimensional stability	ISO 23999	≤ 0.2%		
Castor chair	ISO 4918	Pass		
Static electrical propensity	ISO 6356/AATCC 134	Antistatic ≤ 2.5kV		

Accreditation

Manufactured under accredited ISO 9001 quality, ISO 14001 environmental and ISO 45001 OHS management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit armstrongflooring au or armstrongflooring.co.nz
All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions.

Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.

