

FLAT WEB SLING

SPECIFICATION FOR 6 TONNE - BROWN

**AS
1353.1**



Flat Web Sling - Polyester

Every Austlift flat webbing sling is fabricated using 100% high tenacity polyester yarn. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS1353.1.

Note: Other variations available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 8 x the load indicated
- 2 Ply webbing



WLL 6000KG		
BROWN WIDTH: 180mm		
CODE	LENGTH (M)	Wt. (kg)
910615	1.5	2.18
910620	2.0	2.95
910630	3.0	4.4
910640	4.0	5.3
910650	5.0	6.2
910660	6.0	7.4
910670	7.0	8.63
910680	8.0	9.86
910690	9.0	11
910691	10.0	12.5
910692	12.0	15

WORKING LOAD LIMITS CHART (KG) - (WLLs)								
FLAT WEBBING SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	60°	60° CHOKE
BROWN	6000	4800	12000	10200	8400	6000	10200	8400