

3232VS-XL

| Ethernet - RJ-45

32x32 Composite Video & Analog Balanced Stereo Audio Matrix Switcher



The Lassen XL Series offers flexibility and adaptability to any application where saving space and costs are important. 3232VS-XL is a 32x32 composite video & analog balanced stereo Audio matrix switcher, available in a compact 3RU frame. 3232VS-XL also supports breakaway stereo audio switching whereby the Video, Audio Left and Audio Right can all be routed independently. It offers control via the front panel or remotely via RS-232 or Ethernet

TECHNICAL SPECIFICATIONS

Inputs	32 Composite Video: On BNC connectors
	32 Balanced/Unbalanced Stereo Analog Audio: On 5-pin terminal block connectors
Outputs	32 Composite Video: On BNC connectors
	32 Balanced/Unbalanced Stereo Analog Audio: On 5-pin terminal block connectors
Ports	2 Sync: On BNC connectors
	1 Ethernet: On an RJ-45 connector
	1 RS-232/422: On a 9-pin D-sub connector
	2 RS-485: On male mini-XLR connectors, for control panel
	1 AC Power: On an AC power connector
Video	Video Level: 300mV to 2.5Vpp Max
	Impedance: 75Ω nominal
	Return Loss: <-30dB @ 5MHz
Analog Audio	Input - Max. Source Level +24dBu
	Input - Impedance >20kΩ
	Output - Max. Source Level +24dBu balanced +18dBu unbalanced
	Output - Impedance <50Ω
Enclosure	Size: 19" — 3U — mounts in a standard 19" rack
	Dimensions: 19" x 18.5" x 5.25" W, D, H