



kramer

614R/T

Single-Fiber Detachable DVI Optical Transmitter & Receiver

| DVI



The 614T and 614R are a small and lightweight, detachable optical transmitter and receiver pair. They transmit uncompressed DVI resolutions of up to 1920x1200 at 60Hz using one multimode fiber optic cable with SC connectors. The 614T converts the DVI signal to an optical signal that it transmits to the 614R. The 614R decodes the optical signals back to a DVI signal

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel)

Max. Resolution - Up to WUXGA, 2K or 1080p (XGA not supported)

HDTV Compatible

Not HDCP Compliant

Standards Compliance - Certified for medical applications according to IEC 60601-1-2 (Electromagnetic Compatibility)

Laser Standards Compliance - IEC 60825-1, FDA 21CFR1040; Laser Class 1: Safety of laser products

System Range - Up to 500m (1640ft) (multimode)

EDID Capture - Copies and stores the EDID from a display device (614T)

EMI/RFI Free

Cable - 1 SC multimode fiber optic cable

Power - External power adapters (supplied) or 5V DC from source (auto detect)



kramer

TECHNICAL SPECIFICATIONS

INPUTS:	1 DVI (614T), 1 multimode fiber optic with SC connector (614R)
OUTPUTS:	1 multimode fiber optic with SC connector (614T), 1 DVI (614R)
MAX DATA RATE:	4.95Gbps (1.65Gbps per graphic channel), up to WUXGA, 2K or 1080p @36bit color depth (does not support XGA)
MAX. RANGE:	500m (1640ft) over 50/125 multi-mode fiber at WUXGA (1920x1200), 60Hz refresh rate
POWER CONSUMPTION:	5V DC, 300mA max. (614T); 200mA max. (614R)
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 85%, RHL non-condensing
INCLUDED ACCESSORIES:	Two 5V DC/1A power supplies



kramer

CONFIGURATIONS

614R/T(SET)/US	Single-Fiber Detachable DVI Optical Transmitter & Receiver - US Version
614R/T(SET)/EU	Single-Fiber Detachable DVI Optical Transmitter & Receiver - EU Version

