



KVM Switches

- IP KVM Access, Matrix KVM Access
- DB-15 or Cat6 interface
- Combo USB and PS/2
- DVI and USB



DVI-D KVM

- 12 Port DVI-D KVM Switch works up to 1920 x 1200 resolution
- Supports 1080P Full HD
- Integrates with wide range of CyberView Screen and Keyboard drawers or used as a standalone KVM
- KVM switch ports connect to DVI servers using our 4 in 1 KVM cable consisting of DVI-D + USB + 3.5mm stereo audio at the server end and DVI-D + USB at the KVM port



Cat6 KVM – Matrix

- 16 or 32 port Multi-user Matrix Cat 6 KVM
- Simultaneous access allows up to one local, one remote (300mm) and two IP users on four different KVM ports at any one time
- Plug & play technology provides seamless, secure access over IP via a web browser, allowing control down to bios level
- 8 levels of cascade can be achieved offering control of up to 256 servers from a single top level IP switch



USB Hub KVM

- 8 or 16 Port USB Hub KVM Switch works up to 1920 x 1200 resolution
- Allows the user access to additional USB ports for sharing USB peripherals such as printers, scanners & connection of external hard drive/USB for transfer of data
- With the use of our 2 console or IP version a second user can work securely via a remote Keyboard, monitor and mouse across the World Wide Web using 128 bit secure IP access or remote extender over a 300m Cat6 cable.



Cat6 KVM

- 16 or 32 port
- Single user access, two user over a remote extender, or two user over IP
- Legacy servers can be migrated without replacing switch hardware by using the PS/2, USB or USB DVI dongles at the server end of the installation



[Check out the CyberView KVM video](#)

KVM Switches



DB-15 KVM

- 8 or 16 port KVM switches based on DB-15 interface
- Cost effectively specify the switch to match the exact server configurations using specially designed 3-in-1 KVM cable with USB & PS/2 fly leads
- Connect up to 16 servers on 1 switch
- Additionally, this KVM can be 'stacked' to 8 levels providing access to 128 servers
- Available in single user access, two user over a remote extender, two user IP and Matrix IP



PS/2 DB-15 KVM

- 8 port PS/2 DB-15 KVM Switch works up to 1920 x 1200 resolution
- Mix PS/2, USB and SUN with multi-platform switch capability
- Low cost reliable PS/2 based server management
- No software or drivers required



[Request a Quotation](#)

CyberView™	Matrix Cat6 KVM	Matrix DB-15 KVM	Combo Cat6 KVM	Combo DB-15 KVM	USB Hub KVM	DVI-D KVM	PS2 KVM
Rackmount KVM Switch							
KVM Port						DVI+USB	
Port #	32 / 16	16 / 8	32 / 16 / 8	16 / 8	16 / 8	12	8
Server-side KB/MS	USB / PS2	USB / PS2	USB / PS2	USB / PS2	USB	USB	PS2
Server-side Video	VGA / DVI	VGA	VGA / DVI	VGA	VGA	DVI-D	VGA
Server-side Audio	-	-	-	-	-	Stereo	-
USB Device Port	-	-	-	-	2 x USB 2.0	-	-
Max. Distance from KVM to Server	40M	4.5M	40M	4.5M	4.5M	4.5M	4.5M
Cascade Level	8	8	8	8	-	-	8
On-Screen Menu	✓	✓	✓	✓	✓	-	✓
Simultaneous Users (max.4)	✓	✓	-	-	-	-	-
IP Access Option	✓	✓	✓	✓	✓	-	-
Multi-user Profile	✓	✓	✓	✓	✓	-	-
1U Standalone KVM	✓	✓	✓	✓	✓	✓	✓
KVM module for LCD Console Drawer	✓	✓	✓	✓	✓	✓	✓



DG - 100S Cat6 Dongle



DG - 100 Cat6 Dongle



DG - 100SD Cat6 Dongle



CE-6 Combo KVM



CI-6 DVI-D for DVI KVM



CB-6 USB Hub KVM ONLY

Design. Manufacturing. Global Services