



kramer

FC-6

2-Port Multi-Function Serial/IR Control Gateway

| Ethernet - RJ-45



FC-6 is an RS-232/IR multi-function control gateway, capable of plug and play deployment over a customer Ethernet LAN for remote bidirectional RS-232 and IR emitter control of customer devices. Multiple control clients can be IP-connected to the FC-6 control gateway for concurrent control of two RS-232 or four IR controllable devices, such as AV scalars, video displays, audio amplifiers, and DVD players

FEATURES

Dual-Function I/O Ports - Remote IP-Based control of devices connected to the control gateway dual-function I/O ports, with selectable port configuration to bidirectional RS-232 or IR control

Multiple IP Connected Clients - Remotely connected over customer Ethernet network, concurrently controlling any devices connected to control gateway I/O ports

Easy & Reliable Installation - Plug and Play IP installation with dynamic (DHCP) address resolution and auto device discovery over customer LAN. Resilient powering with USB and optional PSU (not included). Compact, designed for piggy-back installation, such as behind a TV or display, with the ability to draw power from a device USB port

Remote Management - Built-in web UI for remote browser-based management and support, by multiple IP-clients over customer LAN. Easy firmware upgrades, either remotely via customer LAN, or locally via device USB port

Pico TOOLS™ - Mount 4 units side-by-side in a 1U rack space with the recommended rack adapter



kramer

TECHNICAL SPECIFICATIONS

| | |
|---|---|
| PORTS: | 2 RS-232/IR multi-function ports on 3-pin terminal blocks, each selectable as one of: <ul style="list-style-type: none">- 1 bidirectional RS-232 serial- 2 IR emitter ports, 1 Ethernet on an RJ-45 female connector, 1 built-in IR sensor for learning, 1 mini USB connector for local services |
| SUPPORTED SERIAL PORT BAUD RATES: | 1200, 2400, 4800, 9600, 19200, 38400, 57600, 15200bps |
| RS-232 COMMUNICATION: | Transparent up to 115200bps |
| IR EMITTER CABLE RANGE: | 80m (260ft) |
| SUPPORTED IR OUTPUT FREQUENCIES: | 20kHz to 1.2MHz |
| SUPPORTED IR INPUT FREQUENCIES: | 20kHz to 60kHz |
| MAXIMUM DATA HANDLING OF DEVICE: | Up to 150kbps summed on all ports |
| MAXIMUM SIMULTANEOUS IP-CLIENT CONNECTIONS: | 40 |
| POWER SOURCE: | 5V DC, 2A |
| POWER CONSUMPTION: | 5V DC, 300mA |
| ENCLOSURE TYPE: | Pico Tools, aluminum |
| COOLING: | Convection ventilation |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | 3ft USB cable, bracket set |
| OPTIONAL ACCESSORIES: | Power supply unit |
| ENVIRONMENTAL REGULATORY COMPLIANCE: | Complies with appropriate requirements of RoHs and WEEE |
| Product Dimensions | 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H |
| Product Weight | 0.1kg (0.2lbs) approx |
| Shipping Dimensions | 49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15") W, D, H |

Shipping Weight

0.3kg (0.6lbs) approx