



### X124 Single Console

1920 x 1200  
WUXGA



### Drawer Features & Display Benefits

- ▶ 1U 24" widescreen LCD console drawer
- ▶ Support 1920 x 1200 native **WUXGA** Ultra high resolution
- ▶ PIP & Picture by Picture viewing efficiency
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ SUN Micro or MAC keyboard options available
- ▶ New enhanced aesthetics with molded front handle
- ▶ Front USB port for device access ( USB Hub KVM only )

### Options

- 3G / HD / SD-SDI Broadcast-grade input ( w/ speaker )
- HDMI ( w/ speaker )
- DC power : 24V / 48V / 125V / 250V

Ordering Information	Standard ( left side open )	Option ( right side open )
Model	X124	X124R

### Specifications

#### • LCD Panel

Size (diagonal) : 24.1" Widescreen TFT  
 Max resolution : 1920 x 1200  
 Brightness (cd/m2) : 300  
 Backlight : LED  
 Colors : 16.7 M  
 Contrast ratio (typ) : 1000 : 1  
 Viewing angle (H/V) : 178° x 178°  
 Active area (mm) : 518 x 324  
 MTBF (hrs) : 30,000  
 Video input : Standard - DVI-D  
 Option - HDMI ( bundle speaker x 2 )

• **Speaker :** Built-in Dual Stereo Speakers  
 ( HDMI only ) 2W x 2

• **Casing Color :** Black ( RAL 9005 )

• **Power Input :** Auto-sensing 100 to 240VAC,  
 50 / 60Hz

#### • Power Consumption ( single console )

Sreen on : Max. 40W  
 Power saving mode : Max. 5W  
 Power button on : Max. 1W

#### • Environmental

Operating temperature : 0 to 55°C degree  
 Storage temperature : -20 to 60°C degree  
 Operating humidity : 20~90%, non-condensing  
 Storage humidity : 5 ~90%, non-condensing  
 Operating altitude : 16,000 ft  
 Non-operating altitude : 40,000 ft  
 Shock : 10G acceleration ( 11ms duration )  
 Vibration : 5~500Hz 1G RMS random vibration

#### • Regulatory

Safety : FCC & CE certified  
 Environmental : RoHS2 & REACH compliant

#### • Weight ( single console )

Net : 15.3 kgs / 33.7 lbs  
 Gross : 19.5 kgs / 42.9 lbs

#### • Dimensions ( single console )

Product : 441.6 x 700 x 44 mm / 17.4 x 27.6 x 1.73 inch  
 Packing : 595 x 910 x 140 mm / 23.4 x 35.8 x 5.5 inch


### Console Cable

#### CX-6


6 feet DVI-D console cable ( bundle )  
 - DVI-D + USB, server end  
 - DVI-D + DB15 ( USB KB & MS ),  
 console port

### Standard Keyboard

**Ge** G keyboard integrated with touchpad



**Gb** G keyboard integrated with trackball



### Supporting layouts

<b>America</b>		United States			
<b>EMEA</b>					
	United Kingdom	Germany	France	Spain	Norway
	Italy	Russia	Switzerland	Netherlands	Portugal
<b>Asia</b>					
	China	Japan	Korea	Arabia	Turkey

### Keyboard Options

\* US layout only

**Me** Mac keyboard with touchpad



**Se** S keyboard with touchpad

**Mb** Mac keyboard with trackball

**Sb** S keyboard with trackball



# 1U 24" High Resolution LCD KVM Drawer



• **Dimensions ( with KVM )**

Product : 441.6 x 800 x 44 mm / 17.4 x 31.5 x 1.73 inch  
 Packing : 595 x 910 x 140 mm / 23.4 x 35.8 x 5.5 inch

• **Weight**

Net : 16.1 kgs / 35.4 lbs  
 Gross : 22 kgs / 48.4 lbs

• **Power Consumption with KVM integration :**

Screen on : Max. 65W  
 Power saving mode : Max. 30W

• **Casing Color :** Black ( RAL 9005 )

\* For details, please refer to our KVM rear kit user manuals.

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf)

For right side open - Add **R** at the end of the model no.  
 sample : X124-MIP1624R

Matrix DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	X124 - MIP813	X124 - MIP1613	-
	1	1	2	X124 - MIP824	X124 - MIP1624	-
	1	1	0	X124 - M802	X124 - M1602	-
	1	2	0	X124 - M803	X124 - M1603	-
	1	3	0	X124 - M804	X124 - M1604	-

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf)

Combo DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	X124 - IP802	X124 - IP1602	-
	1	1	0	X124 - 802	X124 - 1602	-
	1	0	0	X124 - S801	X124 - S1601	-

Combo DB-15 KVM Cable : CE-6 / 10 / 15 ( 6, 10 or 15 ft )

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf)

For right side open - Add **R** at the end of the model no.  
 sample : X124-1201DR

DVI-D KVM	Local	Remote	IP	12-port	-	-
	1	0	0	X124 - 1201D	-	-

DVI-D KVM Cable : CI-6 / 15 ( 6 or 15 ft )

[www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf](http://www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf)

For right side open - Add **R** at the end of the model no.  
 sample : X124-801HR

USB Hub DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	X124 - IP802H	X124 - IP1602H	-
	1	1	0	X124 - 802H	X124 - 1602H	-
	1	0	0	X124 - 801H	X124 - 1601H	-

USB KVM Cable : CB-6 / 10 / 15 ( 6, 10 or 15 ft )