

Installation Guide

Strobes N' More Purple Series Dash Light




Safety First! Before beginning the installation and/or operation of your LEDs, the installation technician and operator must read this manual in full, *before* installation. This document provides all the necessary information to allow your LED to be properly and safely installed to prevent severe injury or damage.

Proper installation of this product requires the installer to have a good understanding of automotive electronics, systems and procedures. Do not stare directly into these lights. Momentary blindness and/or eye damage could result. Do not install this product or route any wires in the deployment area of your air bag. Equipment mounted or located in the air bag deployment area will damage or reduce the effectiveness of the air bag, or become a projectile that could cause serious personal injury or death. Refer to your vehicle owner manual for the air bag deployment area. The User/Installer assumes full responsibility to determine proper mounting location, based on providing ultimate safety to all passengers inside the vehicle. If this product uses a remote device to activate or control this product, make sure that this control is in an area that allows both the vehicle and the control to be operated safely in any driving condition. Do not attempt to control this in a hazardous situation.

If mounting this product requires drilling holes, the installer must be sure that no vehicle components or other vital parts could be damaged by the drilling process. Check both sides of the mounting surface before drilling begins. Also, de-burr any holes and remove any metal shards or remnants. Install grommets into all wire passage holes. For this product to operate at optimum efficiency, a good electrical connection to chassis ground must be made. The recommended procedure requires the product ground wire to be connected directly to the NEGATIVE (-) battery post or vehicle chassis. Do not attach the NEGATIVE (-) wire to any other existing ground wire. It is recommended that these instructions be stored in a safe place and referred to when performing Maintenance and/or reinstallation of this product. FAILURE TO FOLLOW THESE SAFETY PRECAUTIONS AND INSTRUCTIONS COULD RESULT IN DAMAGE TO THE PRODUCT OR VEHICLE AND/OR SEVERE INJURY TO YOU AND YOUR PASSENGERS!

Windshield Mounting

1. Loosen the adjusting screws located on each end and title the light to the desired angle, then tighten the fixed hitch. through the windows ,to ensure that it is at the most desirable angle, and that the light is not impeded by any obstacles and/or window tinting.



2. (Figure 1)

Note: Suction mounting systems are affected by changes in environmental conditions and should therefore be checked regularly to ensure integrity.

Dual Switch Cigarette Plug (3A fuse inside)

- *The One switch which have LED is Power on/off switch
- *Another switch is pattern switch.
- *Input Wire Length: 4C Cable

Note: The PLUG types do not have synchronization.

NOTE

The W(4)AX series LED head have synchronization\n, please remove the Plug and find the power cord wire below as:

- Red = Positive (need to add 3A Fuse)
- Black = Negative
- Blue = Pattern Switch
- Yellow = Synchronized Function

W(4)AX-41/42/62 Flash Pattern (The device is designed with twenty-five patterns)

- | | |
|--|---|
| P1-Quint Flash75 alternating (Sync) – Default | P14-Action Flash simultaneous |
| P2-Quint Flash75 simultaneous Phase1 (Sync) | P15-Module Flash alternating |
| P3-Quint Flash75 simultaneous Phase2 (Sync) | P16-Module Flash simultaneous |
| P4-Quad Flash75 alternating (Sync) | P17-Action scan |
| P5-Quad Flash75 simultaneous Phase1 (Sync) | P18-Steady with 5 Single and Single POP |
| P6-Quad Flash75 simultaneous Phase2 (Sync) | P19-Steady - 5 single |
| P7-Single Flash75 alternating (Sync) | P20-Steady Burn |
| P8-Single Flash75 simultaneous Phase1 (Sync) | P21-Cycle Flash (Demo mode)-Autorun |
| P9-Single Flash75 simultaneous Phase2 (Sync) | P22-Quad Flash75 (NFPA) |
| P10-Single Flash375 alternating (Sync) | P23-Single Flash75 (CA T13) |
| P11-Single Flash375 simultaneous Phase1 (Sync) | P24-Double Flash75 (CA T13) |
| P12-Single Flash375 simultaneous Phase2 (Sync) | P25-Off |
| P13-Action Flash alternating | |

WARRANTY Provided this product is installed and operated in a manner consistent with its use, Strobes N' More guarantees the dash lights for a period of 5 years from the day of purchase. Units demonstrated to be defective within the warranty period will be repaired or replaced at the seller's discretion. The end user is responsible for shipping / returning the item to Strobes N' More and we will cover the cost of return shipping. International customers are responsible for all shipping charges. Improper installation or use of inappropriate or inadequate wiring or circuit protection causes the warranty to be void. Applying voltage directly to the LED's will cause immediate failure and void the warranty. Damages resulting from improper use and/or accidents are not covered by this warranty. Aluminum will corrode if left in the elements or area of high road salt use. Proper cleaning of the light is essential to keeping the unit in like new condition. Magnets are used to hold the light in place Use of non-compatible components and assemblies may cause damage to the system and/or personal injury, and voids all warranties. Strobes N' More LLC shall in no way be liable for other damages including consequential, indirect or special damages whether loss is due to negligence or breach of warranty. Visit www.StrobesNMore.com/warranty for more information.