

Ixia Net Tool Optimizer 7300 Chassis Family



A New Perspective on Network Visibility

The Network Tool Optimizer (NTO) 7300 chassis family and Ixia's Visibility Architecture provide the most scalable network visibility framework in the industry. Together, they deliver the expandability and management flexibility that easily integrates into any network or data center environment, as well as the control and simplicity necessary to improve the usefulness of existing IT tools.

The NTO 7300 is a chassis that allows for centralized control of your network monitoring system in a single, simple, rack-mountable unit. It combines disparate solutions into a smaller data center footprint – saving power, rack space, and improving ROI.

The NTO 7300 is designed for large enterprises and service providers who need monitoring and network security tools to achieve end-to-end network visibility across both physical and virtual networks, including network traffic from Ixia Phantom Virtual Taps.

It provides network visibility to protect tool investments and scale with the network as monitoring needs grow and change as new applications and security threats emerge.



The NTO 7300 fills the IT and provider network visibility gap, enabling organizations to leverage existing tool investments to achieve total application and network visibility. This new platform helps network teams deliver on their service level agreements (SLA), meet their key performance indicators (KPI), and provide best-in-class end-user service.

It gives you a new perspective on network visibility, without the need for crash carts or change requests, to get the right data to the right tools – right now.

NTO 7303 is the NEBS-level 3 certified version of the 7300.

Key Features

- 7U chassis with 6 line modules
- Up to 384 ports of 10GE
- Up to 96 ports of 40GE
- Up to 12 ports of 100GE
- Up to 192 ports of 10GE AFM
- Redundant supervisors
- Hot-Swap supervisors, fans, power, and modules
- Double-Your-Ports for Advanced Ports
- PTP 1588 Time Stamping
- Multi-user permissions with concurrent access
- Automated filter compiler improves automation and speeds configuration

Performance

- Fully non-blocking 3.8Tb backplane in all line card configurations
- Full line-rate across all ports with filtering enabled
- Port reconfiguration with no performance impact

General Specifications

High-Availability Features

- Redundant, hot-swappable power supply/fan/line modules
- -48V DC or Optional 120-240VAC power input
- Front to back air flow
- Redundant management ports
- Craft interface for out-of-band
- Optional redundant Fabric Modules

Performance

- 1GbE/10GbE/40GbE/100GbE support
- Non-blocking architecture; 3.84Tbps total bandwidth
- Full line-rate across all ports with filtering enabled
- Port reconfiguration with no performance impact

Port Flexibility and Features

- Up to 384 10GbE ports available
- Up to 288 1GbE Copper (6x48 port SFP cards)
- Up to 288 1GbE (6x48 Port SFP cards)
- Up to 288 10GbE (6x48 Port SFP+ cards)
- Up to 96 40GbE (6x16 port QSFP cards)
- Up to 384 10GbE (6x16 port QSFP cards + Breakout Cables)
- Up to 12 100GbE (2xCFP plus 4xQSFP cards)
- Up to 192 10GbE AFM ports (32x10GE AFM plus 4xQSFP cards)
- Ingress/egress port programmability
- Software port licensing
- Port tagging
- Monitoring tool port load balancing (up to 32 ports)
- Application Monitoring with Geolocation**
- Time stamping*
- Burst protection*

Management

- SNMP v1, v2, v3 support
- Local, RADIUS, and TACACS+ support (members and groups)
- Granular access control
- Event monitoring & logging
- Syslog
- IT automation control
- Dual IP-based management ports (RJ45 – 10/100/1000)

Filtering

- Centralized filter templates
- Overlapping filter engine
- Filter parameters (Layer 2-4)
- MAC source/destination address
- VLAN and Ether types
- IP protocol and DSCP/TOS Source/destination IP (IPv4/6)
- UDP, TCP ports
- Layer 7 application**
- Packet de-duplication/trimming*
- Protocol Stripping (GTP, MPLS, VLAN Vntag, VxLAN, and FabricPath)*

Physical Specifications

Size and Weight (7300)

- 7U high rack mountable enclosure
- Dimensions: 12.25"Hx19"Wx28"D (inches)
- Weight: 200.0 lbs (91 kg)

Size and Weight (7303)

- 7U high rack mountable enclosure
- Dimensions: 12.25"Hx19"Wx33.27"D (inches)
- Weight: 203.0 lbs (93 kg)

Power

AC Power (Optional 1U Shelf)

- Input AC Voltage: 90-240 VAC RMS auto-switching removable modules up to four per shelf and up to two shelves.
- Frequency: 50-60Hz
- Nominal power requirement: 6A @ 110 VAC, 600W each x 4
- Maximum power requirement: 11A @ 110 VAC, 1200W
- Heat/power dissipation for system with all 288 ports on the front panel at 100% traffic load: nominally 2500W/9000 BTU/hour

DC Power (Standard)

- Operating input voltage: -40 to -60 VDC
- Nominal current: 40A @ -56 VDC, 2200W

- Maximum operating input current: 100A @ 40 VDC, 4000W
- Heat/power dissipation for system with all 288 ports on the front panel at 100% traffic load: nominally 2200W/9000 BTU/hour – maximum 4000W/17000BTU/hour

Environment Operating Specifications**Temperature**

- Operating: 5°C to 40°C
- Short-term: -5°C to 55°C (not to exceed 96 consecutive hours)
- Short-term with fan failure: -5°C to 40°C (not to exceed 96 hours)

Humidity

- Operating: 5% to 85%, (non-condensing)
- Short-term: 5% to 90% (non-condensing, not to exceed 96 hours)

* Requires optional Advanced Features Module

Regulatory/Safety**North American Safety**

- UL 60950-1, 2nd Edition
- CSA C22.2 No. 60950-1, 2nd Edition

European Safety

- EN60950-1:2006

International Safety

- CB Scheme: IEC 60950-1:2005 2nd Edition

RoHS Compliant**EMI/EMC****North American EMC**

- FCC part 15, Class A (USA)
- ICES-003 Issue 5, Class A (Canada)

European EMC

- EN 300 386 V1.6.1:2012 (Emissions, Immunity)
- EN 55022 (Emissions) *
- EN 61000-3-2 (Harmonics) *

IEC/International EMC

- IEC/EN 61000-4-2:2009 (Electrostatic Discharge Immunity)
- IEC/EN 61000-4-3:2006 +A1:2008 +A2:2010 (Radiated Immunity)
- IEC/EN 61000-4-4 (Transient/Burst Immunity)*
- IEC/EN 61000-4-5:2006 (Surge Immunity)
- IEC/EN 61000-4-6:2009 (Conducted Radio Frequency Immunity)
- IEC/EN 61000-4-8:2010 (Magnetic Field Immunity)

* These standards apply to the external AC power supply unit only

** Requires optional Application and Threat Intelligence Processor

- IEC/EN 61000-4-11 (Voltage Dips, Interruptions and Variations)*

Australian EMC

- AS/NZS CISPR 22:2009 (Emissions)

Japanese EMC

- VCCI Class A (Emissions)

Included Accessories

- Two DC power cords with Fused Plugs
- USB flash drive with activation license key
- Support Rail rack mount kit

Line Module Options**10GE Line Card Specifications**

- Dimensions: 1.75"x17.5"x15" (inches)
- Weight: 14.6 lbs. [6.6kg]

40GE Line Card Specifications

- Dimensions: 1.75"x17.5"x15" (inches)
- Weight: 14 lbs. [6.38kg]

Packet Capture Module Specifications

- Dimensions: 1.75"x17.5"x15" (inches)
- Weight: 17.0 lbs. [7.7kg]

ATI Processor Specifications

- Dimensions: 1.75"x17.5"x15" (inches)
- Weight: 15.0 lbs. [6.7kg]

Supervisor Module Specifications

- Dimensions: 11.75"x5"11.75" (inches)
- Weight: 20.6 lbs. [9.34kg]

High Density Combination Card Specifications

- Dimensions: 1.75"x17.5"x15" (inches)
- Weight: 14.8 lbs. [6.7kg]

7300 Carrier Line Module (AFM Capable)

- Dimensions: 1.75"x17.5"x15" (inches)
- Weight: 18.0 lbs. [8.2kg]

Ordering Information

Part Number	Description
SYS-7300-STD	7300 Series Net Tool Optimizer - base system is the chassis assembly only. This includes the following: 1 7300 chassis (includes six total Fan modules), 2 Supervisor modules, 1 DC power cable with connector, 1 integrated cable guide filter cover
SYS-7300-96X-10G	7300 Series Net Tool Optimizer - Base system includes 96 licensed ports of 10G SFP+ with AC power supply. This includes the following 1 7300 chassis (includes six total Fan modules), 2 Supervisor modules, 1 DC power cable with connector, 1 integrated cable guide filter cover, 2 48-port 10G SFP+ interface modules, and 1 AC power system.
SYS-7300-SSV	7300 Series Net Tool Optimizer - Single Supervisor base system is the chassis assembly only. This includes the following: 1 7300 chassis, 1 Supervisor module, 1 DC power cable with connector.
SYS-7303-STD	7303- Net Tool Optimizer – NEBS level 3 certified base system is the chassis assembly only. This includes the following (1) 7303 chassis (991-0081), (2) supervisor modules (992-0059), (2) DC power entry modules (992-0062), (6) fan modules (991-2013), (1) alarm module (992-0058), (1) filter bezel module (991-2016)
MOD-7300-SUPERVISOR	7300 Supervisor module 7300 Series - Supervisor module provides control and fabric connections between line modules.
MOD-7210-IFMOD-10G	7300 Series- single (1) 48-port interface module - support up to 48 10G SFP/SFP+ ports. Requires port activation license.
MOD-7310-IFMOD-40G	7300 Series- single (1) 16-port 40G QSFP+ module - support up to 16 40G QSFP+ ports. Requires port activation license.
MOD-7211-ATP	7300 Series- Single (1) 48-port Application and Threat Intelligence Processor interface module - supports up to 48 10G SFP/SFP+ ports. Requires activation license for ports and license for ATI Processor application and updates.
MOD-7212-PCM	7300 Series- Single (1) 48-port Packet Capture Module interface module - supports up to 48 10G SFP/SFP+ ports. Requires activation license for ports.
MOD-7300-CARRIER	7300 Series- Carrier Line Module - provides four licensed QSFP ports, and 2 optional cassette slots for advanced hardware features.
MOD-7420-IFMOD-100G	7300 Series - Single 100G port interface cassette - supports a single 100G CFP port. Includes port license for 100G speed. Requires 7300 Carrier Line Module 992-0065 for operation.
MOD-7215-IFMOD-AFM16	7300 Series- 16-Port 10G Advanced Feature Module Cassette. Includes 16 Advanced Feature Port licenses for 1G/10G speed. Requires 7300 Carrier Line Module 992-0065 for operation.
MOD-7311-IFMOD-AF	7300 Series- 8x40G and 16x10G NetPort Advanced Feature Module. Supports 8 40G QSFP+ and 16 10G SFP/SFP+ ports. May be licensed for both standard and advanced features. Licenses are not included.
7300-PTPALARM	7300-Alarm and 1588 (PTP) timestamp source – The module provides physical connections for external alarms and a 1588 timestamp source for the chassis modules
RPS-7300-AC	7300 Series- AC (4800W) remote power supply system for the 7300 chassis. Includes

	the following: 1 rack unit AC power shelf, 4 AC (1200W) power modules, 1 management cable.
RPS-7300-ACMOD	7300 Series- Single AC (1200W) power module for 7300 remote power supply system. Replacement unit for power module in (RPS-7300-AC) 7300 power supply system.
MOD-7300-FANMOD	7300 Series- Single (1) fan module unit
ACC-7300-FILTER	7300 Series- 1 year supply of air filter for the 7300 chassis
LIC-P7300-X48D	7300 Series 10G SFP+ Ports License - quantity Forty Eight (transceivers not included)
LIC-P7300-Q16D	7300 Series- 40G QSFP+ Ports License - quantity Sixty Four (transceivers not included)
LIC-P7300-Q8D-X16D	7300 Series- 40G QSFP+ (8) and 10G SFP+ (16) port license. Enables eight (8) 40G and sixteen (16) 10G ports. (Transceivers not included)
LIC-7300-ATI	7300 Series- ATI (Application and Threat Intelligence) Processor One-Year License. Enables application usage and software updates. Does not enable ports. Application will not function without a valid license installed.
LIC-P7300-Q8D-AN	7300 Series- 40G QSFP (8) Advanced Feature NetPort license. Enables NetPort features on eight (8) 40G ports on the MOD-7311-IFMOD-AF module. Requires standard 40G port licenses.
LIC-P7300-X16D-AN	7300 Series- 10G SFP+ (16) Advanced Feature NetPort license. Enables NetPort features on sixteen (16) 10G ports on the MOD-7311-IFMOD-AF module. Requires standard 10G port licenses.

For more information see <http://www.ixiacom.com/>

This material is for informational purposes only and subject to change without notice. It describes Ixia's present plans to develop and make available to its customers certain products, features, and functionality. Ixia is only obligated to provide those deliverables specifically included in a written agreement between Ixia and the customer.

Ixia Worldwide Headquarters

26601 Agoura Rd.
Calabasas, CA 91302

(Toll Free North America)

1.877.367.4942

(Outside North America)

+1.818.871.1800
(Fax) 818.871.1805

www.ixiacom.com

Ixia European Headquarters

Clarion House, Norreys Drive
Maidenhead SL6 4FL
United Kingdom

Sales +44 1628 408750

(Fax) +44 1628 639916

Ixia Asia Pacific Headquarters

101 Thomson Road
#29-04/05 United Square,
Singapore 307591

Sales +65.6332.0125

Fax +65.6332.0127