



Cast Line Cap

482

Description: Steel end cap for remove and reinstall and block. Perfect for line testing and dependable for pipe-end sealing.

Application: Capping pipe ends.

Key Features:

- No special pipe end preparation required
- Meets applicable AWWA C219 Standards
- Can be custom made to fit unusual applications
- Available in a wide variety of pipe O.D. sizes
- Offset outlet makes it convenient to blow out or drain the pipe line
- Pressure rating depends on many factors. Check with the factory for more details
- Outlet is 2" NPT Standard

Materials Specifications (subject to change):

SLEEVE: Ductile Iron ASTM A-536. Ends have smooth inside taper for uniform gasket seating

GASKETS: Nitrile (Buna N) Certified to NSF®/ANSI 61-G. Compounded to produce superior storage and performance characteristics while resisting water, acids, alkalies, most (aliphatic) hydrocarbons and many other chemicals

Temperature Range: -20°F to 180°F

FOLLOWER FLANGES: Ductile Iron ASTM A536. Designed for high strength/weight ratio

BOLTS & NUTS: High-strength, low alloy Steel with heavy, semi-finished hexagon nuts. Optional: Stainless Steel and carbon Steel ASTM A307 electro-galvanized with di-chromate seal

FINISH: Flexi-Coat® Fusion-Bonded Epoxy Finish

Working Pressure: Up to 250 PSI

Pipe Applications: Cast Iron, PVC, Steel

Sizes (in inches): 2, 2½, 3, 4, 6, 8, 10, 12



THIS PRODUCT DOES NOT RESTRAIN PIPE MOVEMENT. Proper anchoring is required to prevent pipe pullout. Failure to anchor or improper anchoring can result in dangerous pipe content escape, property damage, serious injury, or death. Read the product installation instructions prior to installing this product.

482



Cast Line Cap

NOMINAL PIPE SIZE INCHES	CATALOG NUMBER END CODE	RANGE †† INCHES	OVERALL BOLT & LAYING LENGTH INCHES	5/8" BOLT QUANTITY REQUIRED	SLEEVE LENGTH INCHES	APPROXIMATE SHIPPING WEIGHT - LBS.
2	482-00026306-900	2.34-2.63	8 1/2	2	4	9
2 1/2	482-00028806-900	2.65-2.88	8 1/2	2	4	10
3	482-00031306-900	2.85-3.13	8 1/2	4	4	15
	482-00035006-900	3.44-3.62	8 1/2	4	4	15
	482-00039606-900	3.80-3.96	8 1/2	4	4	15
	482-00041406-900	3.97-4.14	8 1/2	4	4	15
4	482-00045006-900	4.22-4.50	8 1/2	4	5	18
	482-00048606-900	4.46-4.86	8 1/2	4	5	18
	482-00051006-900	4.80-5.10	8 1/2	4	5	18
	482-00054506-900	5.11-5.45	8 1/2	4	5	18
6	482-00066306-900	6.28-6.63	8 1/2	4	5	30
	482-00069606-900	6.56-6.96	8 1/2	4	5	30
	482-00072206-900	6.90-7.22	8 1/2	4	5	30
	482-00076506-900	7.25-7.65	8 1/2	4	5	30
8	482-00086306-900	8.40-8.63	8 1/2	6	5	39
	482-00091106-900	8.54-9.11	8 1/2	6	5	39
	482-00094506-900	9.05-9.45	8 1/2	6	5	39
	482-00098506-900	9.46-9.85	8 1/2	6	5	39
10	482-00100006-900	10.00	9 1/2	6	6	57
	482-00107506-900	10.50-10.75	9 1/2	6	6	57
	482-00116006-900	11.10-11.60	9 1/2	6	6	57
	482-00118806-900	11.65-11.88	9 1/2	6	6	57
	482-00122006-900	11.90-12.20	9 1/2	6	6	57
12	482-00120006-900	12.00	9 1/2	8	6	75
	482-00127506-900	12.50-12.75	9 1/2	8	6	75
	482-00135006-900	13.20-13.50	9 1/2	8	6	75
	482-00137506-900	13.51-13.75	9 1/2	8	6	75
	482-00142006-900	13.90-14.20	9 1/2	8	6	75
	482-00144006-900	14.21-14.40	9 1/2	8	6	75

Pipe end caps must be securely blocked or anchored to prevent them from moving off of the pipe.