SAUTER **HMO**



Digital

Advanced features for professional applications



Category	
Brand	Sauter
Product categoriy	Hardness testing
Product group	Leeb hardness tester
Product family	НМО

Measuring System	
Measuring range [Min] (HLx)	170
Measuring range [Max] (HLx)	960
Readability [d] hardness (HIx)	1
Measuring probe length	14,6 cm
Measuring probe diameter	2 cm
Test object minimum weight [Min]	3 kg
Test object thickness [Min]	3 mm
Hardness scales	HLD
Leeb Hardness Tester sensor type	D
Test block inclusive	✓
Units	HL HV HB HRB HRC MPa
Tolerance (% of [Max])	1%

Tolerance (% of [Max])	1%
Display	
Display type	LCD touch
Construction	
Dimension (W×D×H)	24×83×135 mm
Dimension housing (W×D×H)	24×83×135 mm

plastic

Material housing

Functions	
Function for averaging	✓
Limit-setting function	✓
360° measurement possible	✓
Memory function	✓
Memory - number of results	500
Statistic function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min

Scale - Display type

Approval

calibration

Power Supply	
Supplied power supply	Accu & Power supply
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
Input voltage power supply / power [Max]	110 V - 240 V
Input voltage device / power [Max]	5 V, 1 A
Battery / accumulator type	Li-lon
Battery capacity	1.500 mAh
Battery voltage	3,7 V
Rechargeable battery	3.7 V 1600mAh
Rechargeable battery operating time - backlight off	50 h
Rechargeable battery charging time	8 h

CE mark	✓	
Services (optional)		
Article number for factory	961-131	

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	450×340×165 mm
Shipping method	Parcel service
Net weight approx.	4,6 kg
Gross weight approx.	6 kg
Shipping weight	5,3 kg

1

SAUTER **HMO**



Advanced features for professional applications

Pictograms

STANDARD















OPTION

