

KERN OCM 166

The inverted biological laboratory microscope with fluorescence

KERN



Category

Brand	Optics
Product category	Microscope
Product group	Inverted microscope
Product family	OCM-1

Construction

Dimension (W×D×H)	782×304×530 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	45°
Tube type	Siedentopf
Light distribution	0:100
Contrasting methods	Bright field Phase contrast Fluorescent

Standard objectives	10× 20× 40× PH 20×
---------------------	-----------------------------

Lens quality	Infinity Plan
Nosepiece screw-in locations	5
Centring eyepiece	✓
Interpupillary distance [Min]	48 mm
Interpupillary distance [Max]	76 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular

Ocular type	Eyepiece HWF 10 x / Ø 22mm with anti-fungus, high eye point
-------------	---

Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	22 mm
Ocular diameter	30 mm

Objective

Objectives - Details	Objective Infinity Plan 10 x / 0,25 LWD, Fluor, anti-fungus Objective Infinity Plan 20 x / 0,45 LWD, Fluor, anti-fungus PH-Objective Infinity Plan 20 x / 0,45 LWD, Fluor, anti-fungus Objective Infinity Plan 40 x / 0,65 LWD, Fluor, anti-fungus
Objectives magnifications	10 x / 20 x / 40 x

Illumination

Illuminance	Reflected light Transmitted light
Illumination type incident light	HBO
Illumination type transmitted light	Halogen
Illumination intensity incident light	100 W
Illumination intensity transmitted light	30 W
Illumination dimmable	Transmitted light
Filter possible	✓
Aperture diaphragm	✓
Field diaphragm	✓
Brand of light bulb	Philips

Focussing

Field of view [Min]	0,55 mm
Field of view [Max]	2,2 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Built-in power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO

KERN OCM 166



The inverted biological laboratory microscope with fluorescence

Plug-in power supply / adapter for countries - optional

AUS
UK
US
CH

Input voltage power supply / power [Max]

100 - 240 V

Input voltage device / power [Max]

100 - 240 V

Power socket for mains adapter

Power supply cable

Environmental conditions

Storage temperature [Min]

-5 °C

Storage temperature [Max]

40 °C

Approval

CE mark

✓

Packing & Shipping

Delivery time

2 d

Dimensions packaging (W×D×H)

1050×590×330 mm

Shipping method

Freight

Net weight approx.

22 kg

Gross weight approx.

28 kg

Shipping weight

40,9 kg

Pictograms

STANDARD

