


Product datasheet

Specifications



Easy UPS 3S 15 kVA 400V 3:3 UPS, 1 internal 7Ah modular battery string, expandable to 3

E3SUPS15KHB1

Price* : 99,375.00 ZAR

Overview

Presentation	Easy-to-install, easy-to-operate, easy-to-maintain, and easy-to-service 15 kVA, 400V 3-phase UPS. With advanced product features, competitive specifications, and robust electrical design, the Easy UPS 3S UPS makes business continuity easy for small and medium data centers and electrical rooms. Includes dust filter and conformance-coated boards for harsh environments, and 1 internal 7Ah modular battery string, expandable to 3 strings for extended runtime.
Lead time	Usually Ships within 6 Weeks

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	15 kW
Rated power in VA	15 kVA
Provided equipment	Dust filter Installation guide

Physical

Colour	White (RAL 9003)
Height	140 cm
Width	38 cm
Depth	92.8 cm
Net weight	436 kg
USB compatible	Yes

Input

Maximum input current	28 A
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.9 leading to 0.9 lagging
Input Power Factor at Full Load	0.99
Input voltage limits	304...477 V

* Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Network frequency	45...65 Hz
-------------------	------------

Output

Maximum configurable power in VA	15 kVA
Maximum configurable power in W	15 kW
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load
Output voltage tolerance	+/- 1.5 %
UPS type	Double conversion online
Additional information	UPS weight does not include battery weight.

Conformance

Product certifications	CE EAC RCM
Standards	IEC 62040-1-1 IEC 62040-2 IEC 62040-3 IEC 62040-4 ISTA 2B

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	60 dBA
Heat dissipation	852 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	VRLA
Battery voltage	240 V
Maximum short-circuit current	10 kA
Number of battery filled slots	1
Number of battery free slots	2

Packing Units

Package 1 Weight	481 kg
Package 1 Height	164 cm
Package 1 width	56.3 cm
Package 1 Length	101.4 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
-----------------	---