

EN-DLSMR15T

Project	•••
Fixture Type	•••

Product Description:

These $Blox^{M}$ fixed round surface mount LED downlights are an ideal alternative for applications where recessed downlights are not an option. Available in a choice of three wattages and sizes in a white finish.

Comments
Prepared By

Product Image:



Product Feature:


- Energy efficient surface mount LED downlights ideal for concrete ceilings or areas where you are unable to use recessed fittings
- IP54 rated ideal for high rise residential balcony areas
- Wide 100° beam angle
- 3 year warranty

Compliance & Approvals:





Product Dimension:



Product Specs:

Input Voltage	200~240V AC
Power Factor	0.9
Dimmable	Yes
Dimensions	mm (L) x mm (W) x 68mm (H) x 150mm (OD) x mm (RD) x mm
Number of LEDs	72

SKU Table and Ordering

SKU Code	Colour	lm	Wattage	Lumens/Watt	Product Type
EN-DLSMR15T/30	3000	1250	15	83.33	Dimmable
EN-DLSMR15T/40	4000	1400	15	93.33	Dimmable



Warranty

This product has a warranty period of 3 Yearsfrom the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in animproper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

ZA Sales & Distribution Building 6 Pinewood Office Park 33 Riley Road, Woodmead Gauteng South Africa Tel : +27 (0) 11 234 4878