



### Technical Specifications

Wave type	Pure Sine Wave
Rated capacity	1500VA
Voltage Window (Eco mode)	100V-290V
Voltage Window (UPS mode)	180V-260V
Solar Charge Controller rating	40Amp / 24V
Protection	Short-circuit, Overload, High temperature, Internal fault, Deep discharge, Battery low
Solar panel	Supports up to 1000Wp, 24V solar panel array Voc required between 36V to 45V
Battery	24V operating voltage: 100Ah to 200Ah Supports tubular, Flat plate, GEL / VRLA battery
Output	DC output: 12V DC, 5A AC output: 230V, 50Hz

### Display Indications

Mains available	Yes
Battery charging through mains or solar panel	Yes
Input Voltage regulation Mode	Yes
Power savings	Yes
Load output through Battery	Yes
Low battery indication	Yes
Overload indication	Yes
Buzzer sound indications	Battery ON, Low battery pre-alarm, Battery low shut down, Overload shutdown indication, Short circuit & ECO / UPS mode selection

### Environmental

Operating temperature	0 to 45° C
Relative humidity	95% RH non condensing

### Mechanical

Dimensions in mm (L X W X H)	375 x 315 x 150 mm
Net Weight	15.66 Kg
Gross Weight	16.9 Kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. Specifications are subject to change in the course of the development.