



PratiKa wander plug - straight - 125 A - 3P + E - 200...250 V AC - IP67

81391

V	a	ır

Range	PratiKa
Product or component type	Wander plug
Device short name	PratiKa plug
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary	
Plug, socket, control station shape	Straight
[In] rated current	125 A
[Ue] rated operational voltage	200250 V
Network frequency	50/60 Hz
Ground lug clockwise position	9 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: nickel plated brass
Connections - terminals	Captive screws
Cable cross section	1670 mm²
Cable outer diameter	2648 mm
Cable entry	Cable gland
Thread type	Pg 48
Net weight	1.323 kg
Height	325 mm
Width	131 mm
Depth	131 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue

Environment

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP67 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Operating altitude	2000 m
Ambient air temperature for operation	35 °C (86400 s) -2540 °C

Packing Units

Number of Units in Package 1 1	
Package 1 Weight 1.514 kg	
Package 1 Height 12.9 cm	
Package 1 width 12.9 cm	
Package 1 Length 30.6 cm	

Offer Sustainability

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
Yes
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Product Environmental Profile

Contractual warranty

Warranty 18 months
