Product data sheet

Specifications





PratiKa industrial socket - 16 A - 3P + E - 380...415 V AC - IP67

83158

Main

| Range | PratiKa |
|---------------------------|----------------|
| Product or component type | Socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| Mounting mode | Wall-mounted | |
|-------------------------------------|---|--|
| Plug, socket, control station shape | Angled | |
| [In] rated current | 16 A | |
| [Ue] rated operational voltage | 380415 V | |
| Network frequency | 50/60 Hz | |
| Ground lug clockwise position | 6 h | |
| Plug, socket material | Housing: self-extinguishing engineering polymer | |
| Contacts material | Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel | |
| Connections - terminals | Captive screws, completely loosened | |
| Cable cross section | 14 mm² | |
| Cable outer diameter | 815 mm | |
| Cable entry | Cable gland | |
| Thread type | Pg 16 | |
| Net weight | 0.338 kg | |
| Base dimension | 80 x 100 mm | |
| Height | 156 mm | |
| Width | 80 mm | |
| Depth | 127 mm | |
| | | |

| Colour | Grey (RAL 7035) | |
|---------------------------------------|--|--|
| Voltage colour | Red | |
| | | |
| Environment | | |
| Standards | EN 60309-2 EN 60309-1 | |
| IP degree of protection | IP67 conforming to IEC 60529 | |
| IK degree of protection | IK08 conforming to EN 62262 | |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 | |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C | |
| Ambient air temperature for operation | 35 °C (86400 s) | |
| Packing Units | | |
| Unit Type of Package 1 | PCE | |
| Number of Units in Package 1 | 1 | |
| Package 1 Weight | 300.0 g | |
| Package 1 Height | 8.1 cm | |
| Package 1 width | 12.7 cm | |
| Package 1 Length | 15.5 cm | |
| Unit Type of Package 2 | BB1 | |
| Number of Units in Package 2 | 4 | |
| Package 2 Weight | 1.342 kg | |
| Package 2 Height | 15 cm | |
| Package 2 width | 27 cm | |
| Package 2 Length | 21 cm | |
| Unit Type of Package 3 | S03 | |
| Number of Units in Package 3 | 8 | |
| Package 3 Weight | 3.171 kg | |
| Package 3 Height | 30 cm | |
| Package 3 width | 30 cm | |
| Package 3 Length | 40 cm | |
| Offer Sustainability | | |
| Sustainable offer status | Green Premium product | |
| REACh Regulation | REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information | |
| Environmental Disclosure | Product Environmental Profile | |
| | | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| warrantv | 10 HOHUIS |